

4

3

2

1

| PART NUMBER  | A DIA | B DIA | C    | D REF | E    | F DIA | G    | H    | J     | K    | RELEASE           |
|--------------|-------|-------|------|-------|------|-------|------|------|-------|------|-------------------|
| 10-36565-101 | .344  | .250  | .062 | .468  | .344 | .125  | .125 | .062 | .250  | .125 | 24708-41          |
| -121         | .406  | .312  |      |       |      | .125  | .125 |      | .312  | .156 | 24708-41          |
| -122         | .406  | .312  |      |       |      | .188  | .125 |      | .312  | .156 | 24600-4           |
| -141         | .532  | .438  |      |       |      | .125  | .156 | .078 | .438  | .219 | 24708-41          |
| -142         |       |       |      |       |      | .250  |      |      |       |      | 24708-41          |
| -143         |       |       |      |       |      | .312  |      |      |       |      | 24600-4           |
| -161         | .656  | .562  |      |       |      | .250  |      |      | .562  | .281 | 24708-41          |
| -162         |       |       |      |       |      | .312  |      |      |       |      | 24600-4           |
| -163         |       |       |      |       |      | .375  |      |      |       |      | 24708-41          |
| -164         |       |       |      |       |      | .460  |      |      |       |      | 32608-122 PPL     |
| -181         | .719  | .625  |      |       |      | .250  | .219 | .109 | .625  | .312 | 24708-41          |
| -182         |       |       |      |       |      | .375  |      |      |       |      | 24708-41          |
| -183         |       |       |      |       |      | .500  |      |      |       |      | 24600-4           |
| -201         | .844  | .750  | .094 | .532  |      | .250  |      |      | .750  | .375 | 24708-41          |
| -202         |       |       |      |       |      | .500  |      |      |       |      | 24708-41          |
| -203         |       |       |      |       |      | .625  |      |      |       |      | 24600-4           |
| -204         |       |       |      |       |      | .438  |      |      |       |      | 36536-129         |
| -205         |       |       |      |       |      | .312  |      |      |       |      |                   |
| -206         |       |       |      |       |      | .562  |      |      |       |      |                   |
| -221         |       |       |      |       |      | .250  |      |      |       |      | 24708-41 INACTIVE |
| -222         |       |       |      |       |      | .500  |      |      |       |      |                   |
| -223         |       |       |      |       |      | .625  |      |      |       |      |                   |
| -231         | 1.094 | 1.000 |      |       |      | .625  | .281 | .141 | 1.000 | .500 | 32524-172 C2      |
| -232         |       |       |      |       |      | .800  |      |      |       |      | 32524-172 C2      |
| -233         |       |       |      |       |      | .828  |      |      |       |      | 37959-4           |
| -234         |       |       |      |       |      | .375  |      |      |       |      |                   |
| -241         | 1.032 | .938  |      |       |      | .250  |      |      | .938  | .469 | 24708-41          |
| -242         |       |       |      |       |      | .500  |      |      |       |      |                   |
| -243         |       |       |      |       |      | .625  |      |      |       |      |                   |
| -244         |       |       |      |       |      | .750  |      |      |       |      | 24600-4           |
| -245         |       |       |      |       |      | .797  |      |      |       |      | 37959-4           |
| -251         | 1.235 | 1.141 |      |       |      | .750  |      |      | 1.141 | .572 | 32524-172 C2      |
| -252         |       |       |      |       |      | 1.000 |      |      |       | .572 | 32524-172 C2      |
| -253         |       |       |      |       |      | .625  |      |      |       | .571 | 36508-253         |
| -281         | 1.032 | .938  |      |       |      | .250  |      |      | .938  | .469 | 24708-41 INACTIVE |
| -282         |       |       |      |       |      | .500  |      |      |       |      |                   |
| -283         |       |       |      |       |      | .625  |      |      |       |      |                   |

| REL NO. 24600-4 |     | REVISIONS                         |                  |               |
|-----------------|-----|-----------------------------------|------------------|---------------|
| CHG NO.         | SYM | DESCRIPTION                       | DATE             | APPROV.       |
| 47513-25        | A2  | REDRAWN, PPL SAME SIZE            | 8-4-67<br>JAGGER | <i>Jagger</i> |
| 96286           | B   | (CII) REVISED MATERIAL SPEC BLOCK | 7-6-05<br>JED    | <i>JED</i>    |



DRAWING CONTROLLED BY ELECTRICAL CONNECTOR DESIGN GROUP

| ITEM  | QTY REQD | PART NUMBER              | DESCRIPTION                     | NOTE  |
|---|----------|--------------------------|---------------------------------|---|
| <b>PARTS LIST</b>   |          |                          |                                 |   |
| UNLESS OTHERWISE SPECIFIED  |          | DRAWN: B.F.              | DATE: 9-19-49                   | <b>THE Bendix CORPORATION</b><br>ELECTRICAL COMPONENTS DIVISION<br>SIDNEY NEW YORK U.S.A. |
| LINEAR DIMENSIONS ARE IN INCHES.<br>TOLERANCES: .XXX ± .010,<br>.XX ± .03, X ± .1, ANGLES ± 2°<br>OTHER STANDARDS PER 9-3800<br>AND MIL-STD-8. NOTE REF |          | CHECKED: <i>Balantis</i> | DATE: 8-24-67                   |   |
| MATERIAL SPEC SYNTHETIC RUBBER 9-1864   |          | MATERIAL: <i>epoxy</i>   | STANDARDS: <i>Balantis</i>      | TITLE: GROMMET, CABLE CLAMP   |
| PROCESS SPEC  |          | DRAFTING: <i>Stewart</i> | ENGINEERING: <i>J.M. Jagger</i> |   |
| OR<br>9-3764<br>SEE NOTE 1  |          | DEVELOPMENT:             |                                 |   |
| 10-36559<br>10-36560<br>NEXT ASSEMBLY   |          | SIZE: C                  | CODE IDENT NO.: 77820           | 10-36565  |
|   |          | SCALE: NONE              | WT:                             | REF:  |
|   |          |                          |                                 | SHEET 1 OF 2  |

1. ENGINEERING SOURCE APPROVAL REQUIRED.

NOTES:



4

3

2

1

| PART NUMBER  | A DIA | B DIA | C    | D REF | E    | F DIA | G    | H    | J     | K     | RELEASE           |
|--------------|-------|-------|------|-------|------|-------|------|------|-------|-------|-------------------|
| 10-36565-284 | 1.032 | .938  | .094 | .532  | .344 | .750  | .281 | .141 | .938  | .469  | 24708-41 INACTIVE |
| --321        | 1.344 | 1.250 | .125 | .781  | .531 | .375  | .281 | .141 | 1.250 | .625  | 24708-41          |
| --322        |       |       |      |       |      | .625  |      |      |       |       |                   |
| -323         |       |       |      |       |      | .875  |      |      |       |       |                   |
| -324         |       |       |      |       |      | 1.000 |      |      |       |       | 24600-4           |
| -325         |       |       |      |       |      | 1.062 |      |      |       |       | 38532-36          |
| -326         |       |       |      |       |      | 1.125 |      |      |       |       | 38532-48          |
| -331         | 1.625 | 1.531 |      |       |      | 1.250 |      |      | 1.531 | .766  | 32524-172 C2      |
| -332         |       |       |      |       |      | 1.328 |      |      |       |       | 32524-172 C2      |
| -333         |       |       |      |       |      | 1.156 |      |      |       |       | 36536-168         |
| -361         | 1.469 | 1.375 |      |       |      | .625  |      |      | 1.375 | .688  | 24708-41          |
| -362         |       |       |      |       |      | .875  |      |      |       |       |                   |
| -363         |       |       |      |       |      | 1.000 |      |      |       |       |                   |
| -364         |       |       |      |       |      | 1.125 |      |      |       |       | 25600-4           |
| -371         | 1.812 | 1.719 |      |       |      | 1.375 |      |      | 1.719 | .860  | 32524-172 C2      |
| -372         |       |       |      |       |      | 1.469 |      |      |       |       | 36536-102         |
| -373         |       |       |      |       |      | 1.531 |      |      |       |       |                   |
| -401         | 1.719 | 1.625 |      |       |      | .625  |      |      | 1.625 | .812  | 24708-41 C2       |
| -402         |       |       |      |       |      | .875  |      |      |       |       |                   |
| -403         |       |       |      |       |      | 1.000 |      |      |       |       |                   |
| -404         |       |       |      |       |      | 1.125 |      |      |       |       |                   |
| -411         | 2.125 | 2.031 |      |       |      | 1.656 |      |      | 2.031 | 1.016 |                   |
| -441         | 2.369 | 2.219 |      |       |      | 2.000 |      |      | 2.219 | 1.109 |                   |
| -442         |       |       |      |       |      | 1.906 |      |      |       |       | 36524-502         |
| -443         |       |       |      |       |      | 1.750 |      |      |       |       | 36536-129         |
| -481         | 2.588 | 2.438 |      |       |      | 2.000 |      |      | 2.438 | 1.219 |                   |
| -482         | 2.588 | 2.438 |      |       |      | 2.188 |      |      | 2.438 | 1.219 | 38536-119         |

| REL NO. |         | REVISIONS                   |      |          |
|---------|---------|-----------------------------|------|----------|
| CHG NO. | SYM     | DESCRIPTION                 | DATE | APPROVED |
|         | A2<br>B | SEE SHEET 1 FOR ALL CHANGES |      |          |

D

D

C

C

B

B  
E 1036565

A

A

SEE SHEET 1  
NOTES:

10-36560  
10-36559  
NEXT ASSEMBLY

| ITEM   | QTY REQD | PART NUMBER | DESCRIPTION  | NOTE   |
|--|----------|-------------|--|--|
| <b>PARTS LIST</b>  |          |             |  |  |
| UNLESS OTHERWISE SPECIFIED<br>LINEAR DIMENSIONS ARE IN INCHES.<br>TOLERANCES: .XXX ± .010,<br>.XX ± .03, X ± .1, ANGLES ± 2°.<br>OTHER STANDARDS PER 9-3800<br>AND MIL-STD-8. NOTE REF |          |             | DRAWN: B.F.<br>DATE: 10-6-49   | <b>THE Bendix CORPORATION</b><br>ELECTRICAL COMPONENTS DIVISION<br>SIDNEY NEW YORK, U.S.A.<br>TITLE: GROMMET, CABLE CLAMP<br>SIZE: C<br>CODE IDENT NO: 77820<br>10-36565 |
| MATERIAL SPEC  |          |             | CHECKED: <i>Balantini</i><br>DATE: 8-24-67   |  |
| PROCESS SPEC   |          |             | MATERIAL: <i>RPE 8/24/67</i>   |  |
| SEE SHEET 1  |          |             | STANDARDS: <i>Balantini</i><br>DRAFTING: <i>Admet</i><br>ENGINEERING: <i>AMZ</i><br>DEVELOPMENT: |  |
| SCALE NONE   |          | WT          | REF  | SHEET 2  |