



Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS5
Sensor design	Form 8 x 43 x 8
Size	8 mm
Body type	Fixed
Enclosure material	Nickel plated brass
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	0.06 in (1.5 mm)
Discrete output function	1 NO
Discrete output type	PNP
Electrical connection	Cable
Cable length	6.56 ft (2 m)
[Us] rated supply voltage	12...24 V DC
Switching capacity in mA	<= 200 mA
IP degree of protection	IP67

Complementary

Detection face	Lateral center
Detector flush mounting acceptance	Flush mountable
Material	Metal
Front material	PPS
Output circuit type	DC
Cable composition	3 x 0.11 mm ²
Wire insulation material	PvR
Switching frequency	<= 2500 Hz
Marking	CE
Depth	0.31 in (8 mm)
Height	0.31 in (8 mm)
Width	1.69 in (43 mm)
Product weight	0.22 lb(US) (0.1 kg)

Environment

product certifications	UL
ambient air temperature for operation	-13...158 °F (-25...70 °C)

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0836 - Schneider Electric declaration of conformity	Compliant - since 0836 - Schneider Electric declaration of conformity
Available	Available
Available	Available

WARNING: This product can expose you to chemicals including:

Diisononyl phthalate (DINP), which is known to the State Diisononyl phthalate (DINP), which is known to the State of California to cause

of California to cause cancer, and	cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------