







SIGN	DATE	DESCRIPTION	APPROVER
	12/02'08	Flange screw changed from "-" to "+/-"	Tony
	3/11'09	Dim.A & Dim.B Changed	Tony
	2009.12.18	Add UL standard	Jacke
	2010.03.23	Add the 2p mark	Jacke
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item a) Clamp: Steel Zinc plated
- Item b) Terminal(Up body): Thermoplastic (UL94V-0)
- Item c) Terminal(Down body): Thermoplastic (UL94V-0)
- Item d) Female contact: PbBz(CuSn),Tin plated.
- Item e) Terminal screw: Steel Zinc plating "- " slot type
- Item f) Clampage:Steel/steel Zinc plated
- Item g) With flange screw: Steel Zinc plated, M2.5

Electrical: cULus

- Voltage rating: 300V
- Current rating: 20A
- Wire range:
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque: 3.5 Lb.-In.
- Screw: M2.5
- Wire strip length: 8-9mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus

VM xx 0 5 x 3 xxxx G

POLES

02: 02 pole

/// ///

16: 16 pole

Color

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)

- G: Pb<40000ppm

— 0000: “@” Logo (Standard)
(Steel screw plating Cr³⁺)

000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

POLE		2	3	4	5	6	7	8
A		13.24	20.86	28.48	36.10	43.72	51.34	58.96
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34
Tol.		±0.15			±0.20			
POLE	9	10	11	12	13	14	15	16
A	66.58	74.20	81.82	89.44	97.06	104.68	112.30	119.92
B	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.30
Tol.		±0.30			±0.40			



ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	VM 7.62 mm W/ Flange Series						
PART NO.	VMxx05x3xxxxG			DWG NO.	8VM0501		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Jacke 2010.03.23	Jacke 2009.12.18		UNIT: mm	X. ±0.50	
					SCALE: NONE	X.X ±0.30	
				SHEET: 01/01	REV.: F	X.XX ±0.10	
						X° ±1°	