



SIGN	DATE	DESCRIPTION	APPROVER
△	12/02'08	Flange screw changed from "-" to "+/-"	Tony
△	3/11'09	Dim.A & Dim.B Changed	Tony
△	2009.12.18	Add UL standard	Jacke
△	2010.03.23	Add the 2p mark	Jacke

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ② Clamp: Steel Zinc plated
- Item ① Terminal(Up body): Thermoplastic (UL94V-0)
- Item ③ Terminal(Down body): Thermoplastic (UL94V-0)
- Item ④ Female contact: PhBz(CuSn), Tin plated.
- Item ⑤ Terminal screw: Steel Zinc plating "-" slot type
- Item ⑥ Clampage: Steel/steel Zinc plated
- Item ⑦ With flange screw: Steel Zinc plated, M2.5

Electrical: cULus

- Voltage rating: 300V
- Current rating: 20A
- Wire range:
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque: 3.5 Lb-In.
- Screw: M2.5
- Wire strip length: 8-9mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus

VM xx 0 5 x 3 xxx G

- POLES ————
- 02: 02 pole
 -
 - 16: 16 pole
- Color ————
- 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange(RAL2011/P)
 - 4 Yellow(RAL1018/A)
 - 5 Green(RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey(RAL7035/D)
- G: Pb<40000ppm
- 0000: "@" Logo (Standard) (Steel screw plating Cr³)
 - 000A: "ANYTEK" Mark
 - Any special item by customer request. please contact sales department.

POLE	2	3	4	5	6	7	8	
A	13.24	20.86	28.48	36.10	43.72	51.34	58.96	
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	
Tol.	±0.15			±0.20				
POLE	9	10	11	12	13	14	15	16
A	66.58	74.20	81.82	89.44	97.06	104.68	112.30	119.92
B	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.30
Tol.	±0.30			±0.40				

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		VM 7.62 mm W/ Flange Series									
PART NO.	VMxx05x3xxxxG	DWG NO.	8VM0501								
APPROVED		CHECKED	Jacke 2010.03.23	DESIGNED	Jacke 2009.12.18	DRAWN		CUST NO.		Tolerance	X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
								SHEET: 01/01		UNIT: mm SCALE: NONE REV.: F	