

Note: This datasheet may be out of date

Please download the latest datasheet of NCU15WF104J6SRC from the official website of Murata Manufacturing

Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=NCU15WF104J6SRC

NCU15WF104J6SRC












Appearance & Shape







- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).



Limited Usage	Automotive Grade
Other Usage	1. Variousengine control units 2. ABS control unit 3. High power devices (IGBT) 4. Temperature compensation for various circuits required high temperature.



Packaging Information

Packaging	Specifications	Minimum Order Quantity
RC	180mm Paper Tape	10000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with no ur sales representatives or product engineers before ordering.

2. This datasheet has early being passifications because there is no expense for datafacturing the product of the product of

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/09/14



Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ NCU15WF104J6SRC \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15WF104J6SRC

NCU15WF104J6SRC



Resistance (25°C)	100kΩ
Resistance Value Tolerance (at 25°C)	±5%
B-Constant (25/50°C)	4250K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	4303K
B-Constant(25/85°C)(Reference Value)	4311K
B-Constant(25/100°C)(Reference Value)	4334K
Max. Voltage	5V
Maximum Operating Current (25℃)	0.032mA
Typical Dissipation Constant (25°C)	1mW/℃
Operating Temperature Range	-40℃ to 150℃
Size Code (in mm)	1.0x0.5mm
Size Code (in inch)	0.4x0.2inch
Shape	SMD
Mass	0.0012g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/


Last updated :2019/09/14


Note: This datasheet may be out of date.

 $\underline{ \text{Please download the latest datasheet of NCU15WF104J6SRC from the official website of Murata Manufacturing} \\$ Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15WF104J6SRC

NCU15WF104J6SRC







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

