



# Series 152, 156, and 157 In-Line Jumpers on 0.100 [2.54] Centers

## FEATURES

- Au-plated End Connectors with Solid Brass Pins on 0.100 [2.54] Centers
- Available Single-ended (Series 156), Double-ended (Series 157), or Bare-ended (Series 152)
- Reliable, Electronically-tested Solder Connections
- Easy Identification and Tracing with 10-color Cable

## GENERAL SPECIFICATIONS

- HOUSING: natural UL 94-HB Nylon 6/6
- HEADER PINS: Brass, 1/2-hard
- PIN PLATING: 10μ [0.25μ] min. Au per MIL-G-45204 over 50μ [1.27μ] min. Ni per SAE AMS-QQ-N-290B
- CABLE INSULATION: UL Style 1061 Polyvinyl Chloride (PVC), semi-rigid
- LAMINATE: clear PVC, Self-extinguishing
- CONDUCTORS: 26-AWG, 7/34-strand, tinned Cu per ASTM B 33 Series 152 Conductors are not pre-tinned. Consult factory for pre-tinned, bare-ended jumpers
- CABLE CURRENT RATING: 1 amp at 10°C [50°F] above ambient
- CABLE VOLTAGE RATING: 300V
- CABLE TEMPERATURE RATING: 176°F [80°C]

## MOUNTING CONSIDERATIONS

- SUGGESTED PCB HOLE SIZE: 0.033 ± 0.002 [0.86 ± 0.05] dia.



## ORDERING INFORMATION


**XX-XXX-XXX**

Series  
 156 = Single-ended\*  
 157 = Double-ended\*  
 152 = Bare-ended

Cable Length "L" (inches)  
 1.00" = 001 (min)  
 1.25" = 001.25  
 1.50" = 001.5  
 Etc.

No. of Conductors  
 (4 thru 8)

\* Not Available in RoHS



No. of Conductors	Min. Insulation Length
4 thru 8	1.00 [25.40]
9 and 10	1.25 [31.75]
11 thru 22	1.50 [38.10]

"A" = (NO. OF CONDUCTORS x 0.100 [2.54]) + 0.040 [1.02]  
 "B" = (NO. OF CONDUCTORS - 1) x 0.100 [2.54]  
 "W" = (NO. OF CONDUCTORS x 0.100 [2.54]) - 0.020 [0.51]

ALL DIMENSIONS: INCHES [MILLIMETERS]  
 ALL TOLERANCES: ±0.005 [0.13] UNLESS OTHERWISE SPECIFIED  
 FOR PRE-TINNED, BARE-ENDED JUMPERS, CONSULT FACTORY  
 CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS

CUSTOMIZATION: ARIES SPECIALIZES IN CUSTOM DESIGN AND PRODUCTION. SPECIAL MATERIALS, PLATINGS, SIZES, AND CONFIGURATIONS CAN BE FURNISHED, DEPENDING ON QUANTITY.  
 ARIES RESERVES THE RIGHT TO CHANGE PRODUCT GENERAL SPECIFICATIONS WITHOUT NOTICE  
 PRINTOUTS OF THIS DOCUMENT MAY BE OUT-OF-DATE AND SHOULD BE CONSIDERED UNCONTROLLED



2609 Bartram Road • Bristol, PA 19007-6810 USA  
 TEL 215-781-9956 • FAX 215-781-9845  
 WWW.ARIESELEC.COM • INFO@ARIESELEC.COM

