



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	10/17/97	<i>[Signature]</i>
B	PER EC 0U20-0692-00	9/28/01	<i>C. Hoang</i> 9/28/01

NOTE:

FREQUENCY RANGE: dc - 6 GHz
 VSWR: 1.17:1 MAX.
 INSERTION LOSS: 0.4 dB MAX
 IMPEDANCE: 50 ohm
 INSULATION RESISTANCE: 5,000 Megaohm MIN
 WORKING VOLTAGE: 500 V_{rm} MIN
 DWV: 1,500 V_{rm} MIN AT SEA LEVEL
 CORONA LEVEL: 375 V MIN AT 70,000 FEET
 TEMPERATURE RANGE: -65 TO +165°C

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
RETAINING RING	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		
FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°
DRAWN BY KYLE LE 7-03-97		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
CHECKED BY		
APPD BY <i>[Signature]</i> 10/17/97		AMP TITLE 'OST' PLUG TO 'OSN' PLUG HIGH FREQ ADAPTER SIZE B CODE IDENT NO. 26805 3681-2311-02 REV 01 ₀ SCALE 3:1 SHEET 1 OF 1
USE ASSY PROCEDURE NO. A.P. N/A		

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

CUSTOMER DRAWING

AMP PART # 1058662-1
 SHEET 1 OF 1 REV B