

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

APRIL ,2004.

© COPYRIGHT 2004 By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

A1

REVISED PER ECO-11-005033

01APR11

RK

HMR

NOTES:

1

SINGLE PACK IN ACCORDANCE WITH SPEC 107-3275

2

100 TRAY PACK IN ACCORDANCE WITH SPEC 107-3275

3

0.08μm Au PLATING OVER 1.27μm Ni PLATING

4

0.08μm Au PLATING OVER 1.27μm Ni PLATING OVER 0.76μm Cu PLATING

5

0.76μm Au PLATING OVER 1.27μm Ni PLATING OVER 0.76μm Cu PLATING

6

PASSIVATED

7

WHITE BRONZE PLATING

8

PLATING AS PER BODY, EXCEPT FOR PASSIVATED WHICH IS NICKEL PLATED

9

HAND TOOL 9-1478240-0

10

DIE SET 9-1478248-0

11

FOR TECHNICAL DATA REFER TO YOUR LOCAL TE CONNECTIVITY SALES OFFICE

12

ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED

16.5±0.5

12.6

13.3±0.3

1.60

2.50 REF.

8.0 HEX. A/F

SOLDER

1

2

3

4

5

6

7

9

9.50

3.00

4.00

8

RECOMMENDED CRIMP SLEEVE A/F HEX

3.45

RECOMMENDED CABLE STRIPPING DIM'S

1.00

5.00

10.50

1	1	-	-	-	-	-	-	BRASS	7	CAP	9
-	-	1	1	-	-	-	-	BRASS	4	CAP	9
-	-	-	-	1	1	-	-	STAINLESS STEEL	6	CAP	9
-	-	-	-	-	-	1	1	STAINLESS STEEL	3	CAP	9
1	1	1	1	1	1	1	1	BRASS	8	CRIMP SLEEVE	8
1	1	-	-	-	-	-	-	BRASS	7	SHELL	7
-	-	1	1	-	-	-	-	BRASS	4	SHELL	7
-	-	-	-	1	1	-	-	STAINLESS STEEL	6	SHELL	7
-	-	-	-	-	-	1	1	STAINLESS STEEL	3	SHELL	7
1	1	1	1	1	1	1	1	SILICON		GASKET	6
1	1	1	1	1	1	1	1	STAINLESS STEEL		CIRCLIP	5
1	1	1	1	1	1	1	1	PTFE		INSULATOR	4
1	1	-	-	-	-	-	-	BRASS	7	BODY	3
-	-	1	1	-	-	-	-	BRASS	4	BODY	3
-	-	-	-	1	1	-	-	STAINLESS STEEL	6	BODY	3
-	-	-	-	-	-	1	1	STAINLESS STEEL	3	BODY	3
1	1	1	1	1	1	1	1	BRASS	5	CENTER CONTACT	2
1	1	-	-	-	-	-	-	BRASS	7	BODY	1
-	-	1	1	-	-	-	-	BRASS	4	BODY	1
-	-	-	-	1	1	-	-	STAINLESS STEEL	6	BODY	1
-	-	-	-	-	-	1	1	STAINLESS STEEL	3	BODY	1
4--1	4--0	3--1	3--0	2--1	2--0	1--1	1--0	MATERIAL		DESCRIPTION	ITEM
2	1	2	1	2	1	2	1				
QUANTITY PER ASSY									PARTS LIST		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

FINISH

± -

± -

± -

± -

± -

± -

-

DWN

R.SMITH

04FEB04

CHK

S.PARLOW

04FEB04

APVD

F.WHEELER-KING

04FEB04

PRODUCT SPEC

108-3460

APPLICATION SPEC

411-3276

WEIGHT

-

CUSTOMER DRAWING

STE

TE Connectivity

NAME

SMA RIGHT ANGLE CRIMP ATTACHMENT

CAPTIVE CONTACT

RG174A/U, 188A/U, 316/U, KX3B, KX22A

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-1478924

-

SCALE

1:1

SHEET

1 OF 1

REV

A1

1470-19

(3/11)