

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

**Part Number:** [75235-2185](#)  
**Status:** **Active**  
**Overview:** [GbX® Backplane Connector System](#)  
**Description:** 4-Pair GbX® Backplane Connector System, Left Guide Header, 80 Circuits, Gold (Au)  
0.76µm,Pin Length 5.55mm

**Documents:**  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)  
[Product Specification PS-75221-999 \(PDF\)](#)

**Agency Certification**

UL E29179

**General**

Product Family Backplane Connectors  
Series [75235](#)  
Application Backplane  
Application Tooling Documents TM-622022099  
Comments Left Guide Header, Keying Position H  
Component Type PCB Header  
Overview [GbX® Backplane Connector System](#)  
Product Name GbX®  
UPC 822350175715

**Physical**

Circuits (Loaded) 80  
Circuits (maximum) 80  
Color - Resin Gray (Dark)  
Durability (mating cycles max) 200  
First Mate / Last Break No  
Flammability 94V-0  
Guide to Mating Part Yes  
Keying to Mating Part Yes  
Material - Metal High Performance Alloy (HPA), Stainless Steel  
Material - Plating Mating Gold  
Material - Plating Termination Tin-Lead  
Material - Resin High Temperature Thermoplastic  
Net Weight 4.537/g  
Number of Columns 10  
Number of Pairs 4  
Number of Rows 8  
Orientation Vertical  
PC Tail Length 2.20mm  
PCB Locator No  
PCB Retention Yes  
PCB Thickness - Recommended 1.60mm  
Packaging Type Tray  
Pitch - Mating Interface 1.85mm  
Pitch - Termination Interface 1.85mm  
Plating min - Mating 0.762µm  
Plating min - Termination 0.762µm  
Polarized to PCB No  
Stackable Yes  
Surface Mount Compatible (SMC) Yes  
Temperature Range - Operating 105°C  
Termination Interface: Style Through Hole - Compliant Pin




image - Reference only

Series

**EU RoHS**  
**ELV and RoHS**  
**Compliant**  
**REACH SVHC**  
Not Reviewed  
**Low-Halogen Status**  
**Not Reviewed**

**China RoHS**



**Need more information on product environmental compliance?**  
  
Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)  
  
Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**  
[75235Series](#)

**Mates With**  
[75220 GbX® Daughtercard](#)

| Application Tooling   <a href="#">FAQ</a>                                                                                                                                       |                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document. |                            |
| Global                                                                                                                                                                          |                            |
| Description                                                                                                                                                                     | Product #                  |
| Insertion Tool, 4-pair by 10-Wide                                                                                                                                               | <a href="#">0622022000</a> |
| Insertion Tool, 4-pair by 20-Wide                                                                                                                                               | <a href="#">0622022010</a> |
| Single Pin Repair Tool                                                                                                                                                          | <a href="#">0622022090</a> |
| Shield Removal Tool                                                                                                                                                             | <a href="#">0622022100</a> |

**Electrical**

|                               |                     |
|-------------------------------|---------------------|
| Current - Maximum per Contact | 1.0A                |
| Data Rate                     | 8.0 Gbps            |
| Real Signals (per 25mm)       | 108                 |
| Shield Type                   | Ground Plane Shield |
| Shielded                      | Yes                 |
| Voltage - Maximum             | 120V AC (RMS)/DC    |

**Material Info**

**Reference - Drawing Numbers**

|                       |                            |
|-----------------------|----------------------------|
| Product Specification | PS-75221-999               |
| Sales Drawing         | SD-75235-210, SD-75838-210 |

GbX is a registered trademark of Amphenol Corporation.

This document was generated on 04/20/2015

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**