Product datasheet
Characteristics

XGSZ09L5

Main

Range of product	OsiSense XG
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	Pre-wired M12 female connector
Accessory / separate part destination	For 24 V DC supply of connection box
Cable length	16.4 ft (5 m)

Complementary

Product compatibility	TCSAMT31FP XGSZ33ETH
Electrical connection	1 female connector M12 4 pins (A coding)
Color	Black
Product weight	0.6 lb(US) (0.27 kg)

Environment

|	
IP degree of protection	IP67

Offer Sustainability

Not Green Premium product	Not Green Premium product
Will be Compliant on 4Q2013	Will be Compliant on 4Q2013 Will be Compliant on 4Q2013
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months

Wiring Diagram

Modbus Connections

Pin no.		Signal
1	Red	+ 24 VDC
2	NC	-
3	Black	0 VDC

4	NC	-