MALE PCB PINS

PRINTED CIRCUIT PINS • NAIL HEAD TYPE

2650
2650-0-00-XX-00-00-33-0
Solder mount in .029 mounting hole

.072 DIA.
.025 DIA.
.022
.272

9872
9872-0-00-XX-00-00-33-0
Solder mount in .049 mounting hole

.072 DIA.
.045 DIA.
.032
.288

6095
6095-X-00-XX-00-00-38-0
Solder mount in .044 mounting hole

.078 DIA.
.040 DIA.
.020
L

Basic Part Number	Length L
6095-0	.580
6095-1	.475

9228
9228-0-00-XX-00-00-38-0
Solder mount in .044 mounting hole

.078 DIA.
.040 DIA.
.020
.540

6092
6092-0-00-XX-00-00-33-0
Solder mount in .044 mounting hole

.078 DIA.
.040 DIA.
.020
.610

2381
2381-0-00-XX-00-00-33-0
Solder mount in .054 mounting hole
Also available on 16mm wide carrier tape:
1,800 parts per 13" reel.
See page 224.2 for Tape & Reel details

.080 DIA.
.050 DIA.
.010
.155

5062
5062-0-00-XX-00-00-33-0
Solder mount in .029 mounting hole

.085 DIA.
.025 DIA.
.025
.375

4541
4541-0-00-XX-00-00-03-0
Solder mount in .022 mounting hole

.098 DIA.
.018 DIA.
.020
.049

6142
6142-0-00-XX-00-00-33-0
Solder mount in .064 mounting hole

.100 DIA.
.060 DIA.
.020
.610

9022
9022-0-00-XX-00-00-33-0
Solder mount in .066 mounting hole
Also available on 24mm wide carrier tape:
1,500 parts per 13" reel.
See page 224.2 for Tape & Reel details

.125 DIA.
.062 DIA.
.025
.185

SPECIFICATIONS:

Pin Material: Brass Alloy 360, 1/2 Hard
(Except where noted)

Dimensions: Inches

Tolerances On: Lengths: ± .005
Diameters: ± .002
Angles: ± 2°

RoHS-2
2011/65/EU

ORDER CODE: XXXX - 0 - 00 - XX - 00 - 00 - XX - 0

BASIC PART #

SPECIFY PIN FINISH:
- **01** 200 μ" TIN/LEAD OVER NICKEL
- ◆ **80** 200 μ" TIN OVER NICKEL (RoHS)
- ◆ **15** 10 μ" GOLD OVER NICKEL (RoHS)
- ◆ **21** 20 μ" GOLD OVER NICKEL (RoHS)
- ◆ **34** 50 μ" GOLD OVER NICKEL (RoHS)