





REV.	DATE	DESCRIPTION
A	01/10/04	UPDATE DRAWING FORMAT
B	11/16/05	ADD CRIMP NOTES



RECOMMENDED CABLE
STRIPPING DIM'S



NOTE:

1. CRIMPED FERRULE
HEX CRIMP SIZE .320"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex					
8						DRAWN	G.R.S.	11/16/05							
7						CHECKED									
6						ISSUED			PART DESCRIPTION						
5									BNC CRIMP PLUG RG-6/U CABLE – 75 ohms						
4	FERRULE	COPPER	NICKEL	1				PART NO.							
3	CONTACT PIN	BRASS	GOLD	1				112508							
2	INSULATOR	DELRIN	NATURAL	1				DWG. NO.							
1	BODY	BRASS	NICKEL	1				112508.DWG							
	DESCRIPTION	MATERIAL	FINISH	QTY				C:/112/112508.DWG		REV.	B	SIZE	A	SCALE	NA