






REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1570029	2015/05/12	Ruru	Change Logo



Section A-A



Recommended Panel Cut-Out



Notes:

- * Waterproof Rate: IP68
- * Screw Nut: Nylon, Gray
- * Clamp Ring: Nylon, Gray
- * Sealing Nut: Nylon, Gray
- * Gasket: EPDM, Black
- * Seals: EPDM, Black
- * Panel Thickness: 7.5mm max.
- * Cable Range: $\varnothing 6\text{mm} \sim \varnothing 10\text{mm}$
- * Spanner Size:
 - ① Screw Nut: 22mm
 - ③ Body: 22mm
 - ⑤ Sealing Nut: 22~22.9mm

UNIT:mm		TITLE PG 9 Straight with SR		Amphenol LTW		ITEM NO CSG-09G004	DRAWN BY Ruru	DATE 2015-05-12
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 1:1	SIZE A4	SHEET 1 OF 1	安費諾亮泰企業股份有限公司	DWG NO CSG-09G004	CHECKED BY Rita	DATE 2015-05-12
REV. B		WC-REV. A.1	QC: Inspection item		CUSTOMER ALTW	APPROVED BY Lion		DATE 2015-05-12

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.