


6010M, 6011M, 6012M, 6013M and 6091M Series Oil-Tight Non-Relampable Neon-LED Indicator Lights

Description and Features



Solid-state indicator lights complete with built-in current-limiting resistor and rectifier diode.

Meets NEMA Class 13

Mounting: Ø.380(9.65) hole. Supplied with internal tooth lock washer and hex nut.

Wire Leads: Neon Models: No. 18 AWG (105°C) 4.4 (111.8)/4.8 (121.9) long, stripped .43 (10.9)/.57 (14.5)
LED Models: No. 22 AWG (105°C) 4.4 (111.8)/4.8 (121.9) long, stripped .43 (10.9)/.57 (14.5)

Lens: Polycarbonate

Bezel: Polished stainless steel.

Gaskets: Buna-N

Housing: Black Nylon

| Lens Color | Neon Indicator | |
|------------|---------------------------|---------------------------|
| | Model No. (105-125VAC) | Model No. (208-250VAC) |
| Red | 6010M1 | 6011M1 |
| Amber | 6010M3 | 6011M3 |
| Green | 6012M5* | 6013M5* |
| Lamp used | C2A+Resistor | C2A+Resistor |
| Lamp Color | Black | 1 Black/1 Red |

| Lens Color | LED Solid State Indicator | | |
|--------------------------|---------------------------|----------------------|-----------------------|
| | Model No. for 12V | Model No. for 24V | Incorporates LED** |
| Red | 6091M1-12V | 6091M1-24V | 4304H1 |
| Green | 6091M5-12V | 6091M5-24V | 4304H5 |
| Yellow | 6091M7-12V | 6091M7-24V | 4304H7 |
| Internal Resistor (ohms) | 390 | 1000 | - |

* Incorporates G2B lamp and resistor. Underwriters Laboratories (UL) File No. E20356

**Note: Also incorporates IN4004 (400 P.I.V.) rectifier diode. Red lead positive.