


# PIN RECEPTACLES

FOR .065" - .082" DIAMETER PINS

## 0395

0395-X-15-XX-07-XX-10-0

Swage mount in .096 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 0395-1            | .031            | .062     |
| 0395-2            | .062            | .094     |
| 0395-3            | .094            | .125     |
| 0395-4            | .125            | .156     |
| 0395-5            | .188            | .219     |

## 8016

8016-0-15-XX-07-XX-10-0


Press-fit in .131 mounting hole



## 0350

0350-0-15-XX-07-XX-10-0


Hex press-fit in .129±.002 plated through-hole



## 0714

0714-0-33-XX-07-XX-10-0


Wire crimp termination. Accepts wire sizes 14 AWG Max. / 16 AWG Min.



## 8837

8837-0-15-XX-14-XX-10-0

Solder mount in .159 min. mounting hole



### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths: ±.005

Diameters: ±.002

Angles: ± 2°



**ORDER CODE:** XXXX - X - 15 - XX - XX - XX - 10 - 0

**BASIC PART #**

**SPECIFY SHELL FINISH:**

01 200 μ" TIN/LEAD OVER NICKEL

◆ 80 200 μ" TIN OVER NICKEL (RoHS)

◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

01 200 μ" TIN/LEAD OVER NICKEL

◆ 80 200 μ" TIN OVER NICKEL (RoHS)

◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

#07 or #14 CONTACT (DATA ON PAGE 261)

(For alternate contact choices, see group H on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com