

VB RJ45 LaR - DB RJ45 Cat.6A PUR 15m



| | |
|--------------------|---|
| Part number | 09 48 854 7745 150 |
| Specification | VB RJ45 LaR - DB RJ45 Cat.6A PUR 15m |
| HARTING eCatalogue | https://b2b.harting.com/09488547745150 |

Identification

| | |
|--------------------------|---|
| Category | Cable |
| Series | RJ45 |
| Specification | Pre-assembled on both sides |
| Connector 1 | HARTING VarioBoot RJ45 Preferred directions left/right |
| Connector 2 | HARTING DualBoot RJ45 |
| Type of cable | Copper cable (round) |
| Description of the cable | Wiring 1:1 |
| | Halogen-free oil resistant |

Version

| | |
|-----------------|-------------------|
| Number of cores | 8 |
| Core structure | 4x 2 Twisted Pair |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -30 ... +75 °C unmoved |
| | -5 ... +50 °C moved |
| Degree of protection acc. to IEC 60529 | IP20 |
| Cable length | 15 m |
| Transmission characteristics | Cat. 6 _A Class E _A up to 500 MHz |
| Data rate | 10 Mbit/s |
| | 100 Mbit/s |
| | 1 Gbit/s |
| | 10 Gbit/s |

Material properties

| | |
|------------------|--------------------|
| Material (cable) | PUR (polyurethane) |
| Colour (cable) | Yellow |



Pushing Performance

Specifications and approvals

| | |
|----------------|-------------|
| Specifications | IEC 11801 |
| | IEC 61156-6 |

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 1 |
| Country of origin | Czechia |
| European customs tariff number | 85444290 |