


DESIGNED FOR USE WITH RG-188/U FLEX CABLE	
CABLE ENTRY DIAMETER MINIMUM	
FERRULE	.125
CONTACT	.025
HOUSING	.066

LOC	DIST	REVISIONS				
AJ	00	P	LTR	DESCRIPTION	DATE	DWN
			B	REV PER ECO 07-004710	3/9/2007	DW
						APVD
						KW



1052066-1
PART
NUMBER

HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H OR BRASS PER ASTM-B-16	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COMPONENT	MATERIAL	FINISH

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	TEMPERATURE RATING -65°C TO +125°C
Frequency Range (GHz) DC 12.4	Recommended Mating	Vibration MIL-STD-202, Method
Volt Rating (VRMS MAX) @ Sea Level 250	Torque 7-10 In-Lbs	204, Condition D
VSWR 1.15+.02f(GHz)	Mating Characteristics:	Shock MIL-STD-202, Method 213,
Insertion Loss (dB MAX) .07 √f(GHz)	Insertion (MAX Lbs) N/A	Condition I
RF Leakage (dB MIN) -(60-fGHz)	Withdrawal (MIN Oz) N/A	Thermal Shock MIL-STD-202,
Corona, 70,000 Ft (VRMS MIN) 190	Force to Engage and	Method 107, Condition B,
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Disengage (In-Lbs MAX) 2.0	EXCEPT HIGH TEMP +85°C
Contact Resistance (Milliohms MAX)	Center Contact Captivation	Moisture Resistance MIL-STD-202,
Center Contact 3.0	Axial (Lbs) 6.0	Method 106, No Measurements at
Outer Contact 2.0	Radial (In-Oz) 4.0	High Humidity
Cable to Housing 0.5	Cable Retention	Corrosion - MIL-STD-202, Method
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500	Axial Force (Lbs) 20 Min	101, Condition B, 5% salt spray
I.R.(Megohms MIN) 10000	Torque (In-Oz) N/A	
	Weight (Grams) TBD	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN BN 2/13/68	tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105-3608			
DIMENSIONS: INCHES		CHK PRB 2/16/68				
		APVD D.NANIA 2/29/68	NAME			
		PRODUCT SPEC	OSM RIGHT ANGLE CABLE PLUG-SOLDER ATTACHMENT			
MATERIAL		APPLICATION SPEC	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
-		WEIGHT -	A2	00779	C=1052066	-
FINISH		CUSTOMER DRAWING	SCALE 3:1	SHEET 1 of 1	REV B	