


P	LTR	DESCRIPTION	DATE	DWN	APVD
	L	REVISED PER ECO-14-011808	09AUG2014	AP	SB



1. CONNECTOR ACCEPTS SIZE 20 DF SOCKET CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.

2. CONNECTOR COMPLIES WITH 108-40005 WHERE APPLICABLE.

3 GLASS-FILLED PBT OR GLASS-FILLED NYLON, UL94V-0 RATED. COLOR: BLACK

4 STEEL PER ASTM A109.

5 ZINC PLATED PER ASTM B633; TYPE II; CLASS SC1; YELLOW CHROMATE.

6 TIN OR TIN-LEAD PLATED PER MIL-T-10727.

7 TIN PLATED PER MIL-T-10727 OVER COPPER PER MIL-C-14550.

8 ZINC PLATED .000200-.000400 THICK, YELLOW TRIVALENT CHROMIUM CHROMATE COATING.

SUPERSEDED BY 205209-1

OBSOLETE	STANDARD	8	.120	205209-7
	SMALL PACK	5	.120	205209-6
	STANDARD	6	.154	205209-3
	STANDARD	7	.120	205209-2
OBSOLETE	STANDARD	5	.120	205209-1
	PACKAGING TYPE	SHELL FINISH	A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN S.WELDON 7-19-85	TE Connectivity	
	0 PLC ± -	CHK J.GERACE 7-29-85	NAME	
	1 PLC ± -	APVD -	RECEPTACLE CONNECTOR, SIZE 4, 37 POSITION, AMPLIMITE HDP	
	2 PLC ± -	PRODUCT SPEC	SIZE CAGE CODE DRAWING NO	
	3 PLC ± .005	APPLICATION SPEC	A2 00779 C=205209	
MATERIAL SEE NOTES	FINISH SHELLS: SEE TABLE	WEIGHT -	SCALE 4:1	SHEET 1 OF 1
CUSTOMER DRAWING			REV L	