








THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2012/10/22	Ruru	HD20-12PMFS-SS8001 To HD20-12PMFS-SW8001
B	LE31650220	2016/05/03	Vicky	Update Note




Recommend Panel Cut-Out



Assembly Instruction

- Note:**
- * $\varnothing$ Important Dimension
 - * Waterproof Rate: IP68
IP68: 1M depth of water in 24 Hrs.
(防水等級: IP68)
IP68: 水深一米測試24小時
 - * Shell: Zinc Alloy, Electrodeposition Coating, Black.
 - * Insulation: Nylon, Black
 - * Female Pin: Copper Alloy, Gold Plated.
 - * Gasket: Silicone, Gray
 - * Screw: Stainless Steel.
 - * Recommended Panel Thickness 9mm(Max).



UNIT: mm		TITLE		Amphenol LTW		ITEM NO	DRAWN BY	DATE
TOLERANCE		PANEL SCREW 12PIN M CONN F PIN		安費諾亮泰企業股份有限公司		HD20-12PMFS-SW8001	Vicky	2016-05-03
.X	±0.25	SCALE	3:2	SIZE	A4	DWG NO	CHECKED BY	DATE
.XX	±0.1	REV.	B	WC-REV.	A.2	HD20-12PMFS-SW8001	Rita	2016-05-03
.XXX	±0.05	SHEET 1 OF 1		CUSTOMER		ALTW	APPROVED BY	DATE
ANGLES	±1°	QC: Inspection item					Lisa	2016-05-03