XZCPV1041L5



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Electrical connection	M8, 4 pins elbowed female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	16.4 ft (5 m)	
Cable outer diameter	0.18 in (4.6 mm)	_
Cable composition	4 x 0.25 mm ²	
Wire insulation material	PVC	
System Voltage	60 V AC 75 V DC	harain
Line Rated Current	3 A	
Contact resistance	5000 μOhm	
Insulating resistance	1 GΩ	
Product weight	0.43 lb(US) (0.195 kg)	§

Environment


IP degree of protection	IP65 IP67	the near
product certifications	CULus	
ambient air temperature for operation	-13176 °F (-2580 °C) (static)	
ambient air temperature for storage	-13176 °F (-2580 °C)	

Not Green Premium product	Not Green Premium product
Compliant - since 1201 - Schneider Electric declaration of conformity	Compliant - since 1201 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months


Dimensions



L: Lenght of cable

Connections and Schemes

Connector



BN: Brown
BK: Black
BU: Blue
WH: White