




9	FERRULE	BRASS	NICKEL	1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020"	APPROVALS	DATE	Amphenol Connex				
8	CONTACT PIN	PHOSPHOR BRONZE	GOLD	1		DRAWN	M.ZHANG					06/17/10
7	HUT HEX	BRASS	NICKEL	1		CHECKED						
6	LOCK WASHER	BRASS	NICKEL	1		ISSUED			PART DESCRIPTION TNC BULKHEAD CRIMP JACK – 75 OHM (FOR RG–59/U CABLE)			
5	GASKET	RUBBER	RED	1		SHEET	1 OF 1					
4	BARREL	BRASS	NICKEL	1					PART NO. 122163			
3	INSULATOR	PTFE	NATURAL	1								
2	BODY	BRASS	NICKEL	1					DWG. NO. 122163.DWG REV. NC SIZE A SCALE NA			
1	HOUSING	BRASS	NICKEL	1								
	DESCRIPTION	MATERIAL	FINISH	QTY		DO NOT SCALE DRAWING	CAD FILE C:/CONNEX/122163.DWG					