

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

- . -


© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC
HBDIST
—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	CHANGE THE VENT HOLE SHAPE FROM RECTANGLE TO CIRCLE ONE ECO-13-015347	16-DEC-14	XL,Y	B,F
	G1	REMOVE 3-1440002-6, ADD IT TO ANOTHER CD DRAWING ECO-14-011106	18-JUL-14	XL,Y	B,F



NOTES:

1.TERMINAL DIMENSION IS NOT INCLUDING SOLDER TIP.

2.LOT NO. SYSTEM AS FOLLOWING:

0 8 2 5

WEEK

YEAR

3.GENERAL TOLERANCE AS FOLLOW:

TOLERANCE	
0~0.99mm	±0.1
1mm~2.99mm	±0.2
3mm MIN.	±0.3

④ 4.FOR THE TIN-PLATING OF THE PINS:
+0.1mm FOR WIDTH,THICKNESS AND DIAMETER.
+0.5mm FOR LENGTH.

THIS DRAWING IS A CONTROLLED DOCUMENT.


DWN
LIU, DAVEY 13MAY2009CHK
BANGHUA, YUAPVD
SUNNY, ZHANG

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

DIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

MATERIAL

FINISH



TE Connectivity

NAME

OZT-D/LM1 CUSTOMER DRAWING

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C-1461254-2

SCALE 4:1

SHEET 1 OF 2

REV G1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

- . -



COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD



SEE SHEET 1

107-79006

SUPERCED BY 1461392-8	9-1419145-2	OZT-SH-112LM1	OZT-SH-112LM1	12V	32
ACTIVE	2-1419124-7	OZT-SH-124LM1	OZT-SH-124LM1	24V	31
SUPERCED BY 3-1440002-8	3-1419124-4	OZT-SS-148LM1	OZT-SS-148LM1	48V	30
OBSOLETE	3-1419124-3	OZT-SS-124LM1	OZT-SS-124LM1	24V	29
OBSOLETE	3-1419124-1	OZT-SS-112LM1	OZT-SS-112LM1	12V	28
ACTIVE	1-1461392-2	OZT-SH-148LM1	OZT-SH-148LM1	48V	27
ACTIVE	1-1461392-1	OZT-SH-148DM1	OZT-SH-148DM1	48V	26
ACTIVE	1-1461392-0	OZT-SH-124LM1	OZT-SH-124LM1	24V	25
ACTIVE	1461392-9	OZT-SH-124DM1	OZT-SH-124DM1	24V	24
ACTIVE	1461392-8	OZT-SH-112LM1	OZT-SH-112LM1	12V	23
ACTIVE	1461392-7	OZT-SH-112DM1	OZT-SH-112DM1	12V	22
ACTIVE	1461392-6	OZT-SH-109LM1	OZT-SH-109LM1	9V	21
ACTIVE	1461392-5	OZT-SH-109DM1	OZT-SH-109DM1	9V	20
ACTIVE	1461392-4	OZT-SH-106LM1	OZT-SH-106LM1	6V	19
ACTIVE	1461392-3	OZT-SH-106DM1	OZT-SH-106DM1	6V	18
ACTIVE	1461392-2	OZT-SH-105LM1	OZT-SH-105LM1	5V	17
ACTIVE	1461392-1	OZT-SH-105DM1	OZT-SH-105DM1	5V	16
ACTIVE	1-1461254-0	OZT-SS-148DM1	OZT-SS-148DM1	48V	15
ACTIVE	1461254-9	OZT-SS-124DM1	OZT-SS-124DM1	24V	14
ACTIVE	1461254-8	OZT-SS-109LM1	OZT-SS-109LM1	9V	13
ACTIVE	1461254-7	OZT-SS-109DM1	OZT-SS-109DM1	9V	12
ACTIVE	1461254-6	OZT-SS-106LM1	OZT-SS-106LM1	6V	11
ACTIVE	1461254-5	OZT-SS-106DM1	OZT-SS-106DM1	6V	10
ACTIVE	1461254-4	OZT-SS-105LM1	OZT-SS-105LM1	5V	9
ACTIVE	1461254-3	OZT-SS-105DM1	OZT-SS-105DM1	5V	8
ACTIVE	1461254-2	OZT-SS-112DM1	OZT-SS-112DM1	12V	7
ACTIVE	1461254-1	OZT-SS-103DM1	OZT-SS-103DM1	3V	6
ACTIVE	3-1440002-8	OZT-SS-148LM1	OZT-SS-148LM1	48V	5
ACTIVE	3-1440002-7	OZT-SS-124LM1	OZT-SS-124LM1	24V	4
ACTIVE	3-1440002-6	OZT-SS-112LM1	OZT-SS-112LM1	12V	3
SUPERCED BY 1-1461392-0	3-1440002-5	OZT-SH-124LM1	OZT-SH-124LM1	24V	2
SUPERCED BY 1461392-8	3-1440002-4	OZT-SH-112LM1	OZT-SH-112LM1	12V	1
PACKING SPEC.	PART STATUS	TE PART NO	DESCRIPTION	PART A	PART B

(E1)

RELAY TYPE



		UV RESIN	UV SEAL	16
		EPOXY RESIN	SEAL	15
		Cu ALLOY	HINGE SPRING	14
		PBT	CASE	13
		MW79	MAGNETIC WIRE	12
UL94V-0		PET	BASE	11
UL94HB		PBT	BOBBIN	10
	SOLDER DIP	Cu ALLOY	COIL TERMINAL	9
UL94V-0		PPS	CARD	8
		Ag ALLOY	MOVABLE CONTACT	7
		Ag ALLOY	STATIONARY CONTACT	6
	SOLDER DIP	Cu ALLOY	MOVABLE SPRING	5
	SOLDER DIP	Cu ALLOY	NO-TERMINAL	4
	Ni PLATED	STEEL	CORE	3
	Ni PLATED	STEEL	ARMATURE	2
	Ni PLATED	STEEL	YOKE	1
INCOMBUSTIBILITY	TREATMENT	MATERIAL	DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

13MAY2009

CHK

BANGHUA,YU

APVD

SUNNY,ZHANG

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

NAME



TE Connectivity

OZT-D/LM1 CUSTOMER DRAWING

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-1461254-2

-

SCALE 4:1

SHEET 2 OF 2

REV G1