


XVM Supercapacitors

16 V, 65 F module



Description

Eaton supercapacitors are unique, ultra-high capacitance devices utilizing electric double layer capacitor (EDLC) construction combined with new, high performance materials. This combination of advanced technologies allows Eaton to offer a wide variety of capacitor solutions tailored to specific applications.

The 16 V XVM supercapacitor module offers a means to easily achieve higher voltage, power or discharge time through series or parallel connection of multiple modules.

Features

- Compact size for easy mounting as replacement for, or in conjunction with a 12 V battery
- Series or parallel connection of multiple modules for higher voltage, power or discharge time
- High reliability, green solution for pulse or backup power applications
- Maintenance free
- UL recognized

Applications

- Industrial computer and emergency backup energy
- Battery assist engine starting, especially for cold or frequent starts
- Graceful system shutdown for robotics, PLCs and electrical switches

*Supercapacitor lifetimes vary based on charge voltage and temperature. See Eaton's application guidelines or contact your local Eaton sales representative for more information on lifetime estimates



Powering Business Worldwide

Ratings

| | |
|-----------------------------|---------------------|
| Capacitance | 65 F |
| Working voltage | 16.2 V |
| Surge voltage | 17 V |
| Capacitance tolerance | 0% to +20% (+20 °C) |
| Operating temperature range | -40 °C to +65 °C |

Specifications

| Capacitance ¹ (F) | Part number | Maximum initial dc ESR ¹ (mΩ) (Equivalent Series Resistance) | Max continuous current (A) | Max leakage current ¹ (mA) | Max power ² (kW) | Stored energy ³ (Wh) | Typical mass (kg) | Typical thermal resistance ⁴ (°C/W) |
|------------------------------|---------------|--|----------------------------|---------------------------------------|-----------------------------|---------------------------------|-------------------|--|
| 65 | XVM-16R2656-R | 22 | 20 | 23 | 3.0 | 2.4 | 0.75 | 1.5 |

1. Capacitance, ESR and Leakage current are all measured according to IEC 62391-1 at +20 °C
2. Max. Power = Working Voltage² / 4 / DC ESR
3. Stored energy = ½ Capacitance x Working Voltage² / 3600
4. Thermal resistance (Rth) cell body temperature to ambient in open air in degrees C per Watt (°C/W)


Performance

| Parameter | Capacitance change (% of initial value) | ESR (% of initial value) |
|---|--|-----------------------------|
| Life (1500 hours @ +65 °C @ 16.2 Vdc) | ≤ 20% | ≤ 200% |
| Storage life- (Uncharged, non-condensing atmosphere, 1 year @ -40 °C to +70 °C) | ≤ 5% | ≤ 10% |

Safety and certifications

| | |
|-------------------------|---------------------------------|
| Regulatory | UL810A recognized file: MH46887 |
| Environmental | IP54, RoHS, Halogen free |
| Vibration specification | IEC 60068-2-6 |
| Shock specification | IEC 60068-2-27, -29 |
| Cooling | Natural convection |


Dimensions- mm



Mechanical specifications


- Terminal Screws: M5 Philslot,
Nickel-Plated Brass
Max Torque 4N•m
- Mounting Points: Six, Brass Reinforced,
Accommodate M4 Screws,
Min Length 27.5 mm
Max Torque 4N•m
- Mounting Orientation: No Restriction

Wiring configuration examples




Series*

32.4 V, 32.5 F, 20 A



Parallel

16.2 V, 130 F, 40 A



Series/parallel*

48.6 V, 43.3 F, 40 A

* Maximum operating voltage 640 V.

Part numbering system

| XVM | -16R2 | 65 | 6 | -R |
|-------------------|----------------------------|---|------------|------------------|
| Family Code | Voltage (V) R = decimal | Capacitance (μF) | | Standard product |
| | | Value | Multiplier | |
| XVM = Family code | 16R2 = 16.2 V | Example 656 = 65 x 10 ⁶ (μF) or 65 F | | |

Packaging information

- Standard packaging: Bulk, 1 part per box
10 boxes per carton

Part marking

- Manufacturer
- Capacitance (F)
- Working voltage (V)
- Family code (or part number)
- Polarity

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the use.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2019 Eaton
All Rights Reserved
Printed in USA
Publication No. 10105 BU-SB13542
September 2019

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.

Follow us on social media to get the
latest product and support information.

