






REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
S		REVISED PER ECO-17-004657	05APR2017	RS	MZ

- 1
- RECEPTACLE IS LOADED WITH 4 TYPE III+ POSTED PIN CONTACTS.
- 2
- CONTACT BODY: GOLD PER MIL-G-45204 OVER NICKEL PER QQ-N-290.
CONTACT POST: TIN-LEAD PER MIL-T-10727 OVER COPPER PER MIL-C-14550A.
- 3
- CONTACT BODY: GOLD PER MIL-G-45204 OVER NICKEL PER QQ-N-290.
CONTACT POST: TIN OVER COPPER PER MIL-C-14550A.
- 4
- CONTACT BODY: TIN OVER NICKEL PER MIL-C-14550A
CONTACT POST: TIN OVER NICKEL PER MIL-C-14550A



	3	4	.220	YES	NO	1-207825-5
OBSOLETE	3	4	.429	YES	YES	1-207825-4
OBSOLETE	3	4	.119	NO	NO	1-207825-2
OBSOLETE	3	4	.618	NO	YES	1-207825-1
OBSOLETE	3	3	.119	YES	YES	1-207825-0
OBSOLETE	2	3	.119	NO	YES	207825-9
OBSOLETE	2	2	.220	YES	NO	207825-8
OBSOLETE	2	2	.429	YES	YES	207825-7
OBSOLETE	2	2	.119	NO	NO	207825-6
OBSOLETE	2	2	.119	NO	NO	207825-5
OBSOLETE	2	2	.618	NO	YES	207825-4
OBSOLETE	2	2	.119	YES	YES	207825-3
OBSOLETE	2	2	.220	NO	YES	207825-2
OBSOLETE	2	2	.119	NO	YES	207825-1
CONTACT FINISH		A	PERIPHERAL SEAL	THREADED INSERTS	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.LEE BG CHK W.G.LENKER APVD -	7-1-91 4-14-92 -	TE Connectivity		
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-10024	APPLICATION SPEC -	RECEPTACLE ASSEMBLY, POSTED, STD SEX, SERIES 1, 11-4, CPC		
MATERIAL -	FINISH CONTACT: 2	WEIGHT -	SCALE 2:1	SHEET 1 of 1	REV S	RESTRICTED TO -

RECOMMENDED P.C. BOARD LAYOUT