

1 Pt100 KN 3026

The KN Series Ceramic Wire Wound PRTDs are suitable for general applications requiring temperature stability.

Applications: Industrial resistance thermometers, especially in chemical, power generation plants and analytical equipment.

Construction: A platinum coil is sealed inside a high purity aluminum oxide ceramic body. Lead wires are shear force resistant and assure proper connection to extension leads and cables.



Models

| Description | Tolerance IEC 60751 | Order No. | Dimensions mm | | | | Self Heating 0°C (K/mW) | Response time | | | |
|----------------|------------------------|------------|--------------------------------|----------|-----------|----------|----------------------------|---------------------------|------------------|----------------------|------|
| | | | L | D | d | l | | Water current V=0.4m/s | | Air stream V=3m/s | |
| | | | | | | | t _{0.5} | t _{0.9} | t _{0.5} | t _{0.9} | |
| 1Pt100 KN 3026 | W0.3 | 32.206.520 | 30 ⁺³ ₋₀ | 2.6±0.15 | 0.27±0.01 | 10.0±0.5 | 0.4 | 0.3 | 0.6 | 10.5 | 34.0 |
| | W0.15 | 32.206.544 | | | | | | | | | |
| | W0.1 | 32.206.557 | | | | | | | | | |
| | W0.03 | 32.206.082 | | | | | | | | | |

Technical Specification

| | | | |
|---------------------------------|--|--|--|
| Nominal resistance: | 100 Ohm @ 0 °C | Insulation resistance after assembly: | > 100 MOhm @ 25 °C |
| Temperature range: | W0.3 (Class B) = -196 to +660 °C W0.15 (Class A) = -196 to +600 °C (Heraeus exceeds IEC 60751: -100 to +450 °C) W0.1 (Class 1/3 B) = -100 to +350 °C W0.03 (Class 1/10 B) = -50 to +300 °C (Special HST Class proportional to W0.3) | Measuring current: | 1 mA |
| Temperature coefficient: | T _c = 3850 ppm/K | Tolerance class: | - According to IEC 60751:2008 - Other standards and narrower tolerances are available on request |
| Leads: | Palladium-gold alloy | Temperature stability: | Excellent long-term stability |
| | | Also available: | - Platinum-gold alloy - Different temperature coefficients (3916 ppm/K - old JIS) - Extension leads - Two separated coils can be embedded in one ceramic body |

The measuring point is located at 8 mm from the end of the sensor body

Heraeus Sensor Technology USA

1901 Route 130
North Brunswick, NJ 08902
Phone 732-940-4400 Fax 732-940-4445
Email info.hst-us@heraeus.com
www.hst-us.com