

SAFETY ORGANIZATION(S).

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET.

UL 544
CSA 22.2, NO. 0.0.4, 8
VDE 565-3
SEV 1055/TP1977/5.1.1

OPERATING SPECIFICATIONS.

LINE VOLTAGE/CURRENT.

LINE FREQUENCY,
MAX. CASE RISE & RATED CURRENT,
MAX. LEAKAGE CURRENT, EACH
LINE TO GROUND
OPERATING AMBIENT TEMP. RANGE.

6 AMP., 120/250 VAC
6 AMP./40°C, 250 VAC
50-60Hz
40°C
2 µA at 120V 60 Hz
5 µA at 250V 50 Hz
-10°C TO +40°C & RATED CURRENT, I_T
IN AN AMBIENT, T_0 , HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, I_0 , IS AS FOLLOWS:
 $I_0 = I_T \sqrt{\frac{85-T_0}{45}}$
-40°C TO +85°C
21 DAYS @ 40°C 95% RH
6 TIMES RATED CURRENT FOR 8 SECONDS

RELIABILITY SPECIFICATIONS.

STORAGE TEMPERATURE,
HUMIDITY,
CURRENT OVERLOAD TEST.

TEST SPECIFICATIONS.



INDUCTANCE,
CAPACITANCE, (MEASURED @ 1 KHz, 0.25 VAC MAX., 25°C ±1°C)
LINE TO LINE,
DISCHARGE RESISTOR,
LINE/GROUND AND LINE/LINE
INSULATION RESISTANCE
(W/O DISCHARGE RESISTOR)

RECOMMENDED RECEIVING INSPECTION HIPOT.

LINE TO GROUND,
LINE TO LINE,
2250 VDC FOR 1 MINUTE
1450 VDC FOR 1 MINUTE

FILTER APPROVAL.

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.



50Ω - 50a MINIMUM INSERTION LOSS									
FREQUENCY MHz	.15	.2	.5	1.0	10	20	30		
COMMON dB	9	11	16	20	23	20	16		

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM's order or prior written consent.

corcom
LIBERTYVILLE, IL 60048

POWER LINE FILTER

DATE: 9-12-89
REV: 09
SCALE: 1:1
TDL: CW

FINISH:
AS SUPPLIED

AS SUPPLIED