

SIGN	DATE	DESCRIPTION	APPROVER
△			
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

SU Series


Technical Data

Material:	
Pin (outer sleeve) :	Brass,machined, CuZn38Pb2
Clip(contact 6 finger):	Beryllium copper,heat treated or PHBZ
Plating(outer sleeve) :	Tin plated : 2um/80u"nickel,5um/200u"Tin
Plating(contact) :	2um/80 u"nickel,gold or Tin plating
Insulator body(housing) :	PPS. UL94V-0
Electrical	
Current rating :	3 Amps/contact max.
Current resistance :	4m /contact
Insulation resistance :	10000M at 500VAC
Rated voltage :	100VRMS /150Vdc
Mechanical	
Operating temperature :	Gold plated: -55°C to +125°C
(Continuous)	Tin plated: -40°C to +105°C
Average insertion force:	<140g
With steel pin of Ø 0.66mm or SQ 0.64mm	
Average withdrawal force:	>25g
With steel pin of Ø 0.66mm or SQ 0.64mm	
Mechanical life:	min.200
Environmental data	
Solderability (IEC 60068-2-20. Ta) :	235°C, 2s
Resistance to soldering heat (IEC 60068-2-20. Tb) :	
-Through hole mount components	:260°C, 10s

SU - XX 1 0 X 0 XXXXG

No.of contacts :02~80	pin plated: Code	Clip plated	Pin plated	0000	Standard
	0	Gold Flash	Tin 200u"	18H0	Clip 5218 HY ROHS
	1	Gold 10u"	Tin 200u"		
	2	Gold 30u"	Tin 200u"		
	3	Tin 200u"	Tin 200u"		
	4	Gold flash	Gold flash		
	5	Gold 10u"	Gold flash		
	6	Gold 30u"	Gold flash		

N=The number of contacts



P.C.B. LAYOUT

ANYTEK				CUSTOMER COPY					
				ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD					
TITLE		SU Double row Series(10.0mm Pin)							
PART NO.		SUXX10X0XXXXG		DWG NO.		8SU0101			
APPROVED		CHECKED	DESIGNED	DRAWN		CUST NO.		Tolerance	
			Joanna 2005.08.02	Joanna 2005.08.02				UNIT: mm	X. ±0.50
						SCALE: NONE		X.X ±0.30	
						SHEET: 01/01		X.XX ±0.10	
						REV.: C		X* ±1*	