

Fiber optic coupling - FOC-M12-BU/BU - 1416677

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fiber optics coupling M12, duplex, suitable for all fibers, with wall bracket, IP65 degree of protection

M12 OPTIC coupling, suitable for all fiber types

Product Features

- ✓ Pin connector pattern in accordance with DIN/IEC 61754-27
- ✓ Can be used as coupling and panel feed-through
- ✓



Ethernet

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	20.0 GRM
Custom tariff number	85444290
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Fiber	POF, PCF, GOF

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
Degree of protection	IP65/IP67

Material data

Inflammability class according to UL 94	V0
---	----

Fiber optic coupling - FOC-M12-BU/BU - 1416677

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC002641

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Fiber optic coupling - FOC-M12-BU/BU - 1416677

Dimensional drawing

