





R142A.334.161

Series : **ECO BNC 75**

	mm	
A	Maxi 12.9	mini 12.8
B	10.85	10.75



All dimensions are in mm.



COMPONENTS	MATERIALS	PLATING (μm)
BODY	BRASS	NICKEL
CENTER CONTACT	BRONZE	GOLD
OUTER CONTACT		
INSULATOR	PTFE	
GASKET		
OTHERS PARTS	BRASS	NICKEL
-	-	-
-	-	-

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

RADIAL 

STRAIGHT BULKHEAD JACK PANEL SEAL**R142A.334.161****REAR MOUNT FOR CABLE 6/75+93**

Series : ECO BNC 75

PACKAGING

Standard	Unit	Other
100	'W' option	Contact us

SPECIFICATION**ELECTRICAL CHARACTERISTICS**

Impedance		75 Ω
Frequency		0-1 GHz
VSWR	1.3 +	0.00 x F(GHz) Maxi
Insertion loss		0.2 $\sqrt{F}$ (GHz) dB Maxi
RF leakage	- (	NA - F(GHz)) dB Maxi
Voltage rating		500 Veff Maxi
Dielectric withstanding voltage		1500 Veff mini
Insulation resistance		5000 M Ω mini

CABLE ASSEMBLY

Stripping	a	b	c	d	e	f
mm	4.80	8.00	17.5	0.00	12.7	0.00

Assembly instruction :

Crimp 01

Recommended cable(s)

KX 6A

RG 59

Characteristics indicated on this data sheet are those that can be achieved with the highest performance cable. Intrinsic limitations of the cable may diminish the performance of the assembly

Cable retention

- pull off

136 N mini

- torque

NA N.cm**MECHANICAL CHARACTERISTICS**

Center contact retention		
Axial force – Mating end	10	N mini
Axial force – Opposite end	10	N mini
Torque	NA	N.cm mini

Recommended torque

Mating	NA	N.cm
Panel nut	NA	N.cm
Clamp nut	NA	N.cm
A/F clamp nut	0.00	mm

Mating life	100	Cycles mini
Weight	10.50	g

TOOLING

Part Number	Description	Hexagon
.	.	.
R282.235.013	CRIMPING DIES	6.48
R282.223.000	CRIMPING TOOL	6.48
R282.293.000	CRIMPING TOOL M22520/5-01	

OTHER CHARACTERISTICS**ENVIRONMENTAL**

Operating temperature	-40/+85	$^{\circ}$ C
Hermetic seal	NA	Atm.cm3/s
Panel leakage	NA	

Issue : 0909 A

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

