





## Note:

Pro/E File - REV C - 2009-06-09

- I. Material:thermo plastic,ul94 v-0
- 2. Bulkhead thickness range: 0.79-2.54
- 3. Color:black
- 4. Applicable components:
  Applicable power crimp contact: 10132418-\*\*\*\*\*LF
  Applicable contact secondary lock:10073097-DGC001LF
  Applicable signal contact 76347-DGC302LF
  Applicable latch 10066441-DGC001LF for STR version
- 5. Product Spec: GS-12-474
- 6. Application Spec: GS-20-0445
- 7. The part is been sold as loose piece and fci guarantees is the part in compliance with this customer drawing statement. The product spec for cable assemly can be only as the reference document because the testing and spec is based on using fci raw cable and cable assemble. If the raw cable and cable assembly is outside suppliers sourced by cusotmers, customers or cable assembly suppliers should be fully responsible for the cable assy quality.

spec ref	*			dr	Yong Zhang		2015/06/28	proje	ection	1 1	NΛ	size	scale	
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Yong Zhang		2015/07/06	<b>-</b>		MM [		A 4	1:1	
				chr	-		-			-		ecn no -		
	OTTILIN	THERWISE STECTIFED			Opr Guo-Feng Jin		2015/07/06	product	family			rel level	Released	
surface /	linear	0 . X	±0.5			<u>*</u> 85	+5ACP PN	1			0 U			rev
		0.XX	±0.25			± 8S+5ACP PM		<b>/</b>			5 1006	66440-DG	C020ILF	
		0.XXX	±0.10			+ PWRBLADE CABLE HOUSING				\$ □			A	
	angular	0°	±°	www.	fci.com	cat. no	> .	*	Pr	oduct -	Customer	. Drw	sheet 2 of	2

 $\sim$ 

C

opyright FCI

D

PDS: Rev :A

STATUS:Released

Printed: Jul 07, 2015