

PROJECT NR.:		REVISIONS				
PRJ-14-000000805		ÄNDERUNGEN				
P	LYR	DESCRIPTION BESCHREIBUNG	DATE	DWN	APVD	
	A2	DESCRIPTION CORRECTED FROM SOLDER TO SCREW TERMINAL IN TITLE BLOCK	13NOV2014	CR	JK	
	A3	ECR-17-000922, Obsolete PN	29MAY2017	X.X	X.X	
	A4	ECR-18-005237, REACTIVE PN	04APR2018	T.F	C.W	

TECHNICAL DATA	2-2271116-1	2-2271116-2	3-2271116-1	3-2271116-2	4-2271116-1	4-2271116-2	5-2271116-2	6-2271116-2
RATED VOLTAGE	250V	250V	250V	250V	125V	125V	60V	30V
RATED IMPULSE VOLTAGE	2500V	2500V	2500V	2500V	1500V	1500V	800V	500V
POLLUTION DEGREE	3	3	3	3	3	3	3	3
OVERVOLTAGE CATEGORY	II	II	II	II	II	II	II	II
MATERIAL GROUP	II	II	II	II	II	II	II	II
RATED CURRENT	4A	4A	4A	4A	4A	4A	2A	2A
VOLUME RESISTIVITY	≤ 8mΩ	≤ 8mΩ	≤ 8mΩ	≤ 8mΩ	≤ 8mΩ	≤ 8mΩ	≤ 3mΩ	≤ 3mΩ
DEGREE OF PROTECTION	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67
UPPER TEMPERATURE	+85 °C	+85 °C	+85 °C	+85 °C	+85 °C	+85 °C	+85 °C	+85 °C
LOWER TEMPERATURE	-40 °C	-40 °C	-40 °C	-40 °C	-40 °C	-40 °C	-40 °C	-40 °C

1 MATERIAL: ITEM NO. 1: HOUSING - PA
ITEM NO. 2: CONTACT BODY - PA
ITEM NO. 3: CONTACT - CuZn (brass)


2 CONTACT FINISH - CuSnZn (Optalloy)

3 CONTACT FINISH - Au (gold)

4 ALL DIMENSIONS ARE FOR NOMINAL REFERENCE ONLY UNLESS OTHERWISE STATED


5 MEASUREMENT REFERENCE ONLY

6 PACKAGING: 1 PIECE IN A BAG



PIN ARRANGEMENT
A-CODING (SCALE 2:1)

2-2271116-1	2-2271116-2	3-2271116-1	3-2271116-2
4-2271116-1	4-2271116-2	5-2271116-2	6-2271116-2



Reactive	6-8	24 / 0.25mm ²	1 3	12	6-2271116-2
Obsolete	6-8	20 / 0.50mm ²	1 3	8	5-2271116-2
Obsolete	6-8	18 / 0.75mm ²	1 2	5	4-2271116-2
Obsolete	4-6	18 / 0.75mm ²	1 2	5	4-2271116-1
Obsolete	6-8	18 / 0.75mm ²	1 2	4	3-2271116-2
Obsolete	4-6	18 / 0.75mm ²	1 2	4	3-2271116-1
Obsolete	6-8	18 / 0.75mm ²	1 2	3	2-2271116-2
Obsolete	4-6	18 / 0.75mm ²	1 2	3	2-2271116-1
CABLE FEED-THROUGH mm		WIRES AWG / mm ²	MATERIAL	NUMBER OF POLES	TE-PART-NO.

DIESE ZEICHNUNG IST EIN KONTROLLIERTES DOKUMENT. BEMASSUNGEN UND TOLERANZEN GEMAESS GPS (ISO STANDARDS).		DWN YASHKUMAR 25APR2014 CHK M.STRELOW 25APR2014 APVD C.SCHREITLINGER 25APR2014		NAME M12 RECEPTACLE, STRAIGHT, FIELD INSTALLABLE, UNSHIELDED CONNECTOR, SCREW TERMINALS, A-CODING	
THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER GPS (ISO STANDARDS).		PRODUCT SPEC 108-19483 APPLICATION SPEC 114-32127		SIZE A2 CAGE CODE 00779 DRAWING NO. C-2271116	
DIMENSIONS: MASSEINHEITEN: [mm]		TOLERANCES UNLESS OTHERWISE SPECIFIED: ALLGEMEINTOLERANZEN		RESTRICTED TO NUR FÜR	
MATERIAL		WEIGHT GEWICHT		REV A4	
Customer Drawing		/KUNDENZEICHNUNG		SCALE MASSSTAB 2:1 SHEET BLATT 1 OF 1	