

## Cable connector - CA-09P1N8A8007S - 1619523

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable connector, straight, shielded: Yes, SPEEDCON locking, M23, Number of positions: 8+1, Type of contact: Male connector, Crimp connection, Cable diameter: 6 mm ... 10 mm

The figure shows the 6-pos. product version

### Product Features



### Key commercial data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85366990 |
| Country of origin    | Germany  |

### Technical data

#### Temperature range

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

#### Data of the insulating body

|                                                    |                                                                          |
|----------------------------------------------------|--------------------------------------------------------------------------|
| Note                                               | Order information Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately |
| Insulator material                                 | PA 66                                                                    |
| Direction of rotation of contact chamber numbering | Standard                                                                 |
| Coding                                             | N                                                                        |
| Contact connection method                          | Crimp connection                                                         |
| Type of contacts                                   | Male connector                                                           |
| Number of positions                                | 9                                                                        |
| Contact diameter of power contacts                 | 1 mm                                                                     |
| Nominal current per power contact at 25°C          | 8 A                                                                      |

## Cable connector - CA-09P1N8A8007S - 1619523

### Technical data

#### Data of the insulating body

|                                            |       |
|--------------------------------------------|-------|
| Nominal voltage, power contact             | 300 V |
| Contact diameter of signal contacts        | 2 mm  |
| Nominal current per signal contact at 25°C | 20 A  |
| Nominal voltage, signal contact            | 300 V |
| Surge voltage category                     | II    |
| Pollution degree                           | 3     |

#### Housing data

|                                        |                  |
|----------------------------------------|------------------|
| Housing material                       | CuZn, GD-Zn      |
| Type of locking                        | SPEEDCON locking |
| Degree of protection (when plugged in) | IP67             |
| Thread type                            | M23              |

#### Cable seal data

|                     |       |
|---------------------|-------|
| Min. cable diameter | 6 mm  |
| Max. cable diameter | 10 mm |
| Sealing material    | NBR   |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 272607xx |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260702 |
| eCl@ss 7.0 | 27440102 |
| eCl@ss 8.0 | 27440102 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002635 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |

## Cable connector - CA-09P1N8A8007S - 1619523

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 43201404 |
|-------------|----------|

### Approvals

#### Approvals

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

#### Approvals submitted

### Approval details

|                                                                                                   |       |
|---------------------------------------------------------------------------------------------------|-------|
| UL Recognized  |       |
| mm²/AWG/kcmil                                                                                     | 20    |
| Nominal current I <sub>N</sub>                                                                    | 6 A   |
| Nominal voltage U <sub>N</sub>                                                                    | 300 V |


|                                                                                                    |       |
|----------------------------------------------------------------------------------------------------|-------|
| cUL Recognized  |       |
| mm²/AWG/kcmil                                                                                      | 20    |
| Nominal current I <sub>N</sub>                                                                     | 4 A   |
| Nominal voltage U <sub>N</sub>                                                                     | 300 V |

|                                                                                                      |  |
|------------------------------------------------------------------------------------------------------|--|
| cULus Recognized  |  |
|------------------------------------------------------------------------------------------------------|--|

### Drawings

## Cable connector - CA-09P1N8A8007S - 1619523

Schematic diagram



Dimensional drawing

