



**SERIES 20****REED RELAY****REED RELAYS** SERIES 20

**SERIES 20** RELAYS ARE AVAILABLE IN 1A, 2A, 1C, 2C STANDARD DRY REEDS. THEY ARE CONSTRUCTED USING A BOBBIN OF SPECIAL DESIGN MEETING UL94V-0. HIGH QUALITY RHODIUM SWITCHES ARE USED IN ALL IF REQUIRED TO MEET SPECIFIC WELL DEFINED APPLICATIONS.

**USRELAYS** SYSTEMS, PROCEDURES AND CONTROLS MEET MIL-Q-9858-A, AND HAVE BEEN APPROVED BY MAJOR ELECTRONIC COMPANIES AND GOVERNMENTAL AGENCIES. EXTENSIVE EQUIPMENT IS AVAILABLE FOR ON-LINE PRODUCTION TESTING OF ALL REED RELAYS. QUALITY CONTROL PROCEDURES MEET ALL REQUIREMENTS AND PARAMETERS OF MIL-1-45208A.

**CONTACT RATINGS**

PARAMETERS	1 FORM A SPST	2 FORM A SPST	1 FORM C SPDT	2 FORM C SPDT
VOLTAGE (MAX.SWITCHING)	200 VDC	200 VDC	100 VDC	100 VDC
CURRENT (MAX.SWITCHING)	1 AMP	1 AMP	.25 AMP	.25 AMP
POWER (MAX.SWITCHING)	20 WATTS	20 WATTS	5 WATTS	5
CURRENT (MAX.CARRY)	1 AMP	1 AMP	1 AMP	1 AMP
CAPACITANCE (TYPICAL)	.2 PF	.2 PF	.2 PF	.2 PF
CONTACT RESISTANCE (INITIAL)	.100 OHMS	.100 OHMS	.100 OHMS	.100 OHMS
OPERATE TIME (TYPICAL)	.5 MS	.5 MS	.5 MS	.5 MS
RELEASE TIME (TYPICAL)	.25 MS	.25 MS	.25 MS	.25 MS
TEMPERATURE	-55°C TO +85°C	-55°C TO +85°C	-55°C TO +85°C	-55°C TO +85°C
SHOCK	200G @ 11 MS	200G @ 11 MS	200G @ 11MS	200G @ 11MS
VIBRATION	50G @ 0-2000 HZ	50G @ 0-2000 HZ	50G @ 0-2000 HZ	50G @ 0-2000 HZ
INSULATION RESISTANCE	10 <sup>10</sup> OHMS @ 20°C	10 <sup>10</sup> OHMS @ 20°C	10 <sup>9</sup> OHMS @ 20°C	10 <sup>9</sup> OHMS @ 20°C

**DIMENSIONS** UNIT (INCH)

\* FOR .10 OR .15 SPACING SEE ORDERING INFORMATION (BACK)



EXTENSIVE CATALOG INFORMATION ON THE INTERNET  
[WWW.USRELAYS.COM](http://WWW.USRELAYS.COM)



FOR YOUR CONVENIENCE JUST CHARGE IT!

**USRELAYS AND TECHNOLOGY, INC.**  
13851 ROSWELL AVENUE UNITS F/G CHINO, CA. 9171 U.S.A.

TEL (909) 902-5112  
FAX (909) 902-5122  
[WWW.USRELAYS.COM](http://WWW.USRELAYS.COM)