



NOTES:

1. CRIMPED FERRULE HEX CRIMP SIZE 0.213"
2. CONTACT PIN TO SOLDER




132113RPRT		REVISIONS			
DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ.	A	RELEASE TO MFG.	31-Jun-06	NC	G.R.S.
	B	DIMENSIONS UPDATED	20-Jun-11	2176	HR



**RECOMMENDED  
CABLE STRIPPING DIMENSIONS**



SCALE 5.000



CONTACT PIN	BERYLLIUM COPPER	GOLD
INSULATOR	PTFE	NATURAL
BODY	BRASS	GOLD
DESCRIPTION	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL ±.015 (0,381 mm) 3 PLACE DECIMAL ±.005 (0,127 mm) ANGLES ± 1°	MATERIAL	DRAWN HARI R	DATE 20-Jun-11	TITLE SMA REVERSE POLARITY PLUG (FOR RG-58/U CABLE) LEFT THREAD	Amphenol Connex
	REFERENCE TASK# 628	ENGINEER	DATE		
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		APPROVED	DATE		SCALE: 6.0:1
		CAD FILE			DWG SIZE B
					SHEET 1 OF 1
					REV B