



# SENSOR SOLUTIONS FOR AEROSPACE & DEFENSE FROM TE CONNECTIVITY

# SENSOR SOLUTIONS FOR AEROSPACE & DEFENSE FROM TE CONNECTIVITY

TE Connectivity (TE) is one of the largest connectivity and sensor companies in the world. Our broad portfolio of sensor technologies is designed for a wide range of mission critical applications in Aerospace and Defense and other industries. By leveraging our core competencies in high reliability sensors for harsh environments such as Temperature, RFI, EMI, Vibration, and Lightning, we enable our customers to transform their concepts into creations — redefining what's possible using intelligent, efficient and high-performing TE products and solutions.



## SENSOR SOLUTIONS

- FLOW
- FLUID PROPERTY
- FORCE/TORQUE
- HUMIDITY
- LIQUID LEVEL
- RATE/INERTIAL
- POSITION
- PRESSURE
- TEMPERATURE
- ULTRASONIC
- VIBRATION/SHOCK

## QUALITY STATEMENTS

- AS/EN 9100
- ATEX
- ESA/ESCC QUALIFIED
- NADCAP
- ISO 14001
- ISO 9001
- MEASURING INSTRUMENTS  
DIRECTIVE 2004/22/EC ANNEX D
- NASA/GSFC QUALIFIED
- PART21G
- TS 16949

## DESIGN/DEVELOPMENT

- DO-160
- DO-254
- MIL-STD-810
- GRESS

# APPLICATION SOLUTIONS FOR AEROSPACE & DEFENSE

Long development cycles and high qualification costs require aerospace companies to identify stable, reliable, cost-effective partners. TE Connectivity has design engineering groups, as well as AS9100 certified sensor manufacturing facilities, in North America, Europe and Asia Pacific which support Tier 1, 2 and 3 providers with a wide variety of critical sensor solutions for aerospace and defense applications. Regional design and manufacturing allows TE to furnish ITAR free designs and supply products close to our customers' assembly facilities.

## Cockpit Controls

- Automatic autopilot disconnect force sensors
- Motorized potentiometers for position feedback
- Brake pedal position sensors
- Rotary panel switches and sensors
- Force sensors for flight data recording of pilot inputs
- Throttle quadrant position sensors
- Flap and spoiler lever position sensors

## Flight Controls & Actuation

- High lift load sensors
- THSA secondary load path engagement sensors
- Aileron LVDT position sensors
- Resolvers for flap and slat position monitoring
- Force and position sensors for spoiler electro-mechanical actuation
- Brake actuator force sensors for rotorcraft

## Landing Gear & Brakes

- Brake torque sensors
- Pressure sensors for Nose Wheel steering feedback
- Resolvers for steering position
- Load on wheels force sensors
- Centre of gravity force sensors

## Cabin, Galley & Cargo

- Cabin pressure indicator
- Waste tank level sensors
- Environmental cabin control pressure sensors
- Cargo humidity sensors
- Galley temperature sensors
- Air quality temperature sensors
- Oxygen generation pressure transducers

## Launch & Space


- Payload monitoring vibration sensors
- Thrust vectoring LVDT position sensors
- Electrical actuator position resolvers
- Booster separation potentiometers
- Cryogenic fuel pressure transducers
- Satellite temperature sensors
- Mirror/antenna position LVDT sensors

## Engine, Turbine & APU

- Thermocouple harnesses for exhaust gas temperature
- LVDT for thrust reverser position monitoring
- Platinum 200 air temperature sensors
- Variable bleed valve LVDT position sensors
- Rotor track and Balance accelerometers
- Health and Usage Monitoring Systems(HUMS) accelerometers
- Thermistor heater fuel tank level and flow

## Military (Missile, Ground Vehicle, Marine, UAV...)

- Missile fin actuation
- Fuel tank level & flow sensors
- Gun stabilization and shock measurement
- Tamper detection for missiles
- Electronic safe arm and fire
- Oil pressure and temperature sensors
- Airspeed and altitude sensors



## PRESSURE SENSORS

Board Mounted  
mV Output



### MEAS 1230

Package	8 pin DIL
Type	Gage, absolute, differential
Pressure Range	0 - 5 & 10" H <sub>2</sub> O 0 - 0.07, 0.14, 0.35, 1, 2, 3, 7 bar / 0 - 1, 2, 5, 15, 30, 50, 100 psi
Output/Span	50 mV and 100 mV typical
Unique Features	<ul style="list-style-type: none"> <li>• Temperature compensated</li> <li>• High performance UltraStable die Current excitation</li> </ul>
Accuracy	±0.1% Non-linearity
Operating Temp	-40°C to 125°C
Dimensions (mm)	15.2 x 20.3
Typical Apps	Air flow measurement, leak detection, cabin control, ventilation



### MEAS MS52xx, MS54xx

Package	Surface mount
Type	Gage, absolute
Pressure Range	0 - 1, 12 bar / 0 - 15, 174 psi (MS52xx) 0 - 1, 7, 12 bar / 0 - 15, 102, 174 psi (MS54xx)
Output/Span	150 mV, 240 mV
Unique Features	<ul style="list-style-type: none"> <li>• Small size (MS54xx)</li> <li>• High linearity or high sensitivity options</li> <li>• Plastic tube or metal ring options</li> <li>• With gel to protect against moisture</li> <li>• High endurance (Option HM)</li> </ul>
Accuracy	±0.05% or ±0.2% Non-linearity
Operating Temp	-40°C to 125°C
Dimensions (mm)	7.6 x 7.6, height model dependent (MS52xx) 6.4 x 6.2 (MS54xx)
Typical Apps	Absolute pressure sensor systems, engine controls, high resolution altimeters, variometers, barometers

Media Isolated Modules  
Analog Output



### MEAS 89 Button, 89 with Fittings

Package	O-ring mount and threaded / weldable or process fitting
Type	Sealed gage, absolute
Pressure Range	0 - 69, 207, 345 bar / 0 - 1K, 3K, 5K psi
Output/Span	100 mV typical
Unique Features	<ul style="list-style-type: none"> <li>• High pressure, modular design</li> </ul>
Accuracy	±0.25% FSO Non-linearity
Operating Temp	-40°C to 125°C
Dimensions (mm)	89 Button: Ø 9.0 x 7.5 89 with Fittings: Ø 22.2 x 23.6
Typical Apps	Air tank pressure, hydraulics, process control, oxygen generation, inerting systems

## Transducers and Transmitters



### MEAS P900

Package	Threaded ports with stainless steel housing and various heavy duty electrical connections, various electrical outputs
Type	Gage, absolute
Pressure Range	0 - 5 bar to 0 - 689 bar / 0 - 75 psi to 0 - 10K psi
Output/Span	0 - 5 Vdc, 0 - 10 Vdc, 4 - 20 mA
Unique Features	<ul style="list-style-type: none"> <li>• High overpressure (10X over pressure)</li> <li>• Shock &amp; vibration resistant</li> <li>• Heavy Industrial grade transducer</li> <li>• Advanced digital compensation / calibration</li> <li>• Mechanical over pressure stops</li> <li>• High temperature operation</li> </ul>
Accuracy	0.1% to 0.2% FSO
Operating Temp	-54°C to 120°C
Dimensions (mm)	Application dependent
Typical Apps	Hydraulic controls / steering, torpedo depth, vehicle braking systems, drones, weapon systems
Agency Approvals	CE, CENELEC (Intrinsically Safe)



### MEAS M7100, U7100

Package	Automotive grade, stainless steel hermetic pressure ports and integral electrical connector, heavy duty
Type	Gage, no vent gage (M7100) Gage, sealed gage, absolute (U7100)
Pressure Range	0 - 10 thru 0 - 689 bar / 0 - 150 thru 0 - 10K psi (M7100) 0 - 1 thru 0 - 10 bar / 0 - 15 thru 0 - 150 psi (U7100)
Output/Span	0.5 - 4.5 Vdc [Ratiometric Output]; 1 - 5 Vdc [Regulated] (M7100) 0.5 - 4.5 Vdc [Ratiometric Output] (U7100)
Unique Features	<ul style="list-style-type: none"> <li>• 1% total error band (-20°C to 85°C)</li> <li>• Solid state reliability</li> <li>• Survives high vibration and immersion</li> <li>• Microfused technology (M7100)</li> <li>• UltraStable technology (U7100)</li> </ul>
Accuracy	0.25% FSO
Operating Temp	-40°C to 125°C
Dimensions (mm)	26.7 x 26.7 x 50.0
Typical Apps	Military vehicles engine control, compressors, hydraulic
Agency Approvals	CE (EMC), UL 508

## PRESSURE SENSORS

Miniature Transducers and Transmitters



### MEAS XP Series

<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Titanium construction (XP5, XPM4)</li> <li>• Stainless steel housing (XPM6, XPM10)</li> <li>• Amplified output options (XP5, XPM6, XPM10)</li> <li>• Cable and connector options (XPM4)</li> <li>• For static and dynamic applications</li> </ul>
<b>Non Linearity</b>	Up to $\pm 0.25\%$ FSO (XP5, XPM6, XPM10) Up to $\pm 0.35\%$ FSO (XPM4)
<b>Output/Span</b>	20, 30, 75, 100mV (XP5) 30mV, 60mV, 100mV (XPM4) 100mV (XPM6) 50, 100mV (XPM10)
<b>Pressure Range</b>	1 - 345 bar / 15 - 5K psi (XP5, XPM10) 5 - 207 bar / 75 - 3K psi (XPM4) 103 - 1K bar / 1.5K - 15K psi (XPM6)
<b>Overpressure</b>	2X
<b>Operating Temp</b>	-40°C to 120°C
<b>Dimensions (mm)</b>	XP5: Hex 10 XPM4: Hex 8 XPM6: Hex 12 XPM10: Hex 15
<b>Typical Apps</b>	Military and aerospace, explosive test benches, space



### MEAS XPC10

<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Amplified output available</li> <li>• For static and dynamic applications</li> <li>• Optional IP67 ingress protection</li> <li>• High temperature operation</li> </ul>
<b>Non Linearity</b>	Up to $\pm 0.25\%$ F.S.
<b>Output/Span</b>	12mV FSO, 4V FSO (amplified)
<b>Pressure Range</b>	0 - 10, 21, 34, 52, 69, 103, 207, 345, 517 bar / 0 - 150, 300, 500, 750, 1K, 1.5K, 3K, 5K, 7.5K psi
<b>Overpressure</b>	1.5X
<b>Operating Temp</b>	-40°C to 220°C
<b>Dimensions (mm)</b>	Hex 15
<b>Typical Apps</b>	Aerospace, test benches, high frequency / high temperature pressure applications



### MEAS EPIH

<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Diffused silicon diaphragm with a large variety of sizes and shapes available as small as 0.05" outside diameter</li> <li>• High frequency response (to 1.7 MHz)</li> </ul>
<b>Non Linearity</b>	$\pm 1.0\%$ FSO
<b>Output/Span</b>	12 mV to 75 mV
<b>Pressure Range</b>	0 - 0.35, 0.69, 1, 2, 3, 5, 7, 14, 21 bar / 0 - 5, 10, 15, 25, 50, 75, 100, 200, 300 psi
<b>Overpressure</b>	2X to 5X
<b>Operating Temp</b>	-40°C to 120°C
<b>Dimensions (mm)</b>	Application dependent
<b>Typical Apps</b>	Aerospace testing, wind tunnels, aircraft body and wing dynamics

## FORCE / TORQUE SENSORS



### MEAS FN HL Series

<b>Package</b>	Flange mount
<b>Operating Mode</b>	Tension/Compression
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Extremely robust design</li> <li>• Very high EMC/RFI immunity</li> </ul>
<b>Ranges N (Lbf)</b>	Airframe dependent
<b>Output</b>	4/20 mA
<b>Temperature Range</b>	-70°C to +90°C
<b>Dimensions</b>	Airframe dependent
<b>Typical Apps</b>	Measurement of force between geared rotary actuator and slat on high lift systems



### MEAS FN TH Series

<b>Package</b>	Load pin
<b>Operating Mode</b>	Tension
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Built in test feature</li> <li>• Dual redundant</li> <li>• Very high ultimate load</li> </ul>
<b>Ranges N (Lbf)</b>	Airframe dependent
<b>Output</b>	0.5 to 5.5Vdc or 4/20mA
<b>Temperature Range</b>	-70°C to +90°C
<b>Dimensions</b>	Airframe dependent
<b>Typical Apps</b>	Detection of secondary load path engagement on trimmable horizontal stabilizer actuator



### MEAS FN PC Series

<b>Package</b>	Tail stock/control rod
<b>Operating Mode</b>	Tension/Compression
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Compact</li> <li>• Extremely high performance design</li> <li>• Mono or dual channel</li> </ul>
<b>Ranges N (Lbf)</b>	Airframe dependent
<b>Output</b>	0.5 to 10.5Vdc
<b>Temperature Range</b>	-55°C to +55°C
<b>Dimensions</b>	Airframe dependent
<b>Typical Apps</b>	Monitoring of pilot input forces for flight data recording

## FORCE / TORQUE SENSORS



### MEAS FN EM Series

Package	Pancake
Operating Mode	Compression
Unique Features	<ul style="list-style-type: none"> <li>Ultra-flat for integration directly into electro-mechanical actuators</li> </ul>
Ranges N (Lbf)	Airframe dependent
Output	0.5 to 10.5Vdc
Temperature Range	-55°C to 55°C
Dimensions	Airframe dependent
Typical Apps	Compression force measurement electro-mechanical actuators



### MEAS VR BT Series

Package	Pin
Operating Mode	Torque
Unique Features	<ul style="list-style-type: none"> <li>High temperature variable reluctance technology</li> </ul>
Ranges N (Lbf)	Airframe dependent
Output	50mV rms (AC)
Temperature Range	-40°C to 150°C
Dimensions	Airframe dependent
Typical Apps	Monitoring of force brakes



### MEAS FN AF Series

Package	Load pin
Operating Mode	Compression
Unique Features	<ul style="list-style-type: none"> <li>Built in test feature, dual redundant</li> <li>Very high ultimate load</li> </ul>
Ranges N (Lbf)	Airframe dependent
Output	0.5 to 5.5Vdc or 4/20mA
Temperature Range	-70°C to 90°C
Dimensions	Airframe dependent
Typical Apps	Monitoring of force between the electrical actuator and the ailerons

## TEMPERATURE SENSORS

### Sensing Elements



### MEAS Platinum Thin Film Chips

RTD Package	Leadless chips
Type	<ul style="list-style-type: none"> <li>Thin film platinum deposited on ceramic substrate</li> <li>Contact pads on top and bottom side for NTC chip like assembly</li> <li>Contact pads on both ends for SMT</li> </ul>
Resistance Range	100Ω, 1000Ω (Other values on request)
Unique Features	<ul style="list-style-type: none"> <li>Long term stability</li> <li>Interchangeability</li> <li>Assembly like NTC chips</li> <li>Very small dimensions</li> <li>Short response time</li> </ul>
Accuracy	According to DIN EN 60751
Operating Temp	-50°C to +400°C
Dimensions (mm)	1.5 x 1.5 (top / bottom pads) 1.2 x 3.6 (SMT)
Typical Apps	Aerospace, test and measurement



### MEAS Platinum Thin Film Sensors

RTD Package	Wired component
Type	<ul style="list-style-type: none"> <li>Thin film platinum deposited on ceramic substrate, glass coated</li> <li>Tube outline available</li> <li>Connection via radial leads</li> </ul>
Resistance Range	100Ω, 1000Ω (Other values on request)
Unique Features	<ul style="list-style-type: none"> <li>Long term stability</li> <li>Interchangeability</li> <li>Small dimensions</li> <li>Short response time</li> <li>High electrical insulation</li> </ul>
Accuracy	Class T (F0.1), A (F0.15), B (F0.3) according to DIN EN 60751
Operating Temp	-50°C to 600°C (standard) down to -200 °C or up to 1000 °C (on request)
Dimensions (mm)	2.0 x 2.3 x 1.1 (standard) 1.2 x 4.0 x 1.1 (standard) other dimensions (on request)
Typical Apps	Aerospace, test and measurement



### MEAS Glass Wire Wound Sensors

RTD Package	GO, GX
Type	<ul style="list-style-type: none"> <li>RTD</li> <li>Glass rod</li> <li>Radial leads</li> </ul>
Resistance Range	100Ω (2x100Ω on few versions)
Unique Features	<ul style="list-style-type: none"> <li>Aggressive environments (acid, oil, solvent)</li> <li>Small dimensions</li> <li>Stability</li> <li>No hysteresis</li> <li>Short response time</li> <li>Interchangeability</li> </ul>
Accuracy	Class W0.3, W0.15, W0.1 according to IEC60751
Operating Temp	-200°C to 400°C
Dimensions (mm)	Ø 1.8 / Length 5mm to Ø 4.5 / Length 48mm
Typical Apps	Aviation and aeronautics



## TEMPERATURE SENSORS

Sensing Elements



### MEAS Space Qualified (Hi-Rel)

<b>Package</b>	Radial, bead, custom
<b>Type</b>	<ul style="list-style-type: none"> <li>Epoxy</li> <li>Glass</li> <li>Probes</li> <li>ESCC 4006013</li> <li>ESCC 4006014</li> <li>GSFC 319-P18</li> <li>449900 Series</li> </ul>
<b>Resistance Range</b>	1kΩ to 100kΩ
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>ESA and NASA approved</li> <li>High reliability and accuracy</li> </ul>
<b>Accuracy</b>	0.5% to 10%
<b>Operating Temp</b>	-55°C to 115°C
<b>Dimensions (mm)</b>	From 2.4
<b>Typical Apps</b>	Instrumentation and compensation



### MEAS Nickel RTD

<ul style="list-style-type: none"> <li>SOT 23, bare die on request</li> <li>Thin film nickel structure on silicon substrate, protected with a passivation layer</li> <li>SOT23 Package for SMT</li> <li>Good thermal connection of sensing element through leadframe-pin</li> <li>Bare die for COB assembly</li> </ul>
1000Ω
<ul style="list-style-type: none"> <li>Harsh environment compatible</li> <li>Automotive qualified</li> <li>Very small dimensions</li> <li>Very short response time</li> <li>Good linearity</li> <li>High temperature coefficient</li> <li>Low power consumption</li> </ul>
Class B, according to former DIN 43760 standard
-55 °C to 160 °C
2.1 x 2.5 x 2.1 (SOT23), 0.7 x .7 x 0.4 (bare die)
Thermal compensation, thermal management



### MEAS Radial Leaded Thermistors

<ul style="list-style-type: none"> <li>NTC</li> <li>Epoxy or glass coated</li> </ul>
Radial, axial, beads
100 to 1MΩ
<ul style="list-style-type: none"> <li>Interchangeable</li> <li>Moisture resistant</li> <li>Stability</li> </ul>
0.25% to 20%
-55°C to 280°C
0.4 to 4.9
Temperature sensing for OEM



### MEAS Axial Thermistors

<ul style="list-style-type: none"> <li>NTC</li> <li>Glass coated</li> </ul>
DO-35
5kΩ to 100kΩ
<ul style="list-style-type: none"> <li>Tight tolerance (±1%)</li> <li>Max stability using high density (HD) chip</li> <li>Hermetically sealed</li> <li>Tinned &amp; Nickel plated leads</li> </ul>
±1% to ±3%
-40°C to 300°C
2.0 x 4.0 body
Fire detection units, PCB temp sensing

## Sensor Assemblies



### MEAS Thermocouple Probes and Harnesses

Package	Screw-in or push-in design with cable extension, connector, or connecting head
Type	<ul style="list-style-type: none"> <li>Collapsible Mineral Insulated (MI) with alloy sheath (radius≥5*OD)</li> <li>Flexible cable with plastic or composite insulation</li> <li>Rigid protection sheath: ceramic, quartz or alloy sheath</li> </ul>
Sensor Range	Type T, J, K, N, R, S, B (According to TC type and insulation type)
Unique Features	<ul style="list-style-type: none"> <li>High temperature and high vibration level (for MI)</li> <li>Available in small diameters for fast respond time</li> <li>Grounded or ungrounded or apparent hot junction</li> <li>Single or multiple measuring points</li> </ul>
Accuracy	Class 1 according to IEC584
Operating Temp	-40°C to 1700°C (according to TC type and insulation type)
Dimensions (mm)	<ul style="list-style-type: none"> <li>OD Ø0.3 mm to Ø8 mm for MI</li> <li>ø0.15mm for smallest flexible cable</li> <li>Custom dimensions, fittings and cable lengths (from few centimeters to many meters)</li> </ul>
Typical Apps	Engine temperature



### MEAS Surface Sensors

<ul style="list-style-type: none"> <li>RTD: Pt, Ni, Cu</li> <li>Thermocouple: Type J, K, T, E</li> </ul>
Silicone rubber or polyimide laminated element, SP683
<ul style="list-style-type: none"> <li>Flat, flexible, rectangular sensor</li> <li>Variety of designs available</li> </ul>
<ul style="list-style-type: none"> <li>Surface sensing for curved or uneven surfaces</li> <li>Noninvasive, simple installation</li> <li>Adhesive backing option</li> </ul>
RTD: Class A, B according to IEC60751
Varies: -50°C to 200°C Available up to 220°C
Custom dimensions available
Aerospace, motor end windings of stator coils, generators

## POSITION SENSORS

Angular Position Sensors, Encoders Absolute



### MEAS Resolver

Package	Hollow Shaft, Size 15
Range	360 degrees absolute
Output	Analog (sin, cos)
Input Voltage (VR1-R2), Typical	2V rms - 10Vrms
Input Frequency, Typical	4kHz - 20kHz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±7 arcmin to ± 20 arcmin
Pairs of Pole	1 / 3
Maximum Rational Speed	20,000 rpm
Weight	Approx. 90g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Angular position of rotary actuators, rotating shafts



### MEAS Resolver

Package	Hollow Shaft, Size 21
Range	360 degrees absolute
Output	Analog (sin, cos)
Input Voltage (VR1-R2), Typical	2V rms - 12V rms
Input Frequency, Typical	2kHz - 15kHz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±7 arcmin to ± 20 arcmin
Pairs of Pole	1 / 2 / 3 / 4
Maximum Rational Speed	20,000 rpm
Weight	Approx. 240g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Angular position of e-motors (commutation) and permanent magnet generators



### MEAS Resolver

Package	Input Shaft, Integrated Bearing, Size 11
Range	360 degrees absolute
Output	Analog (sin, cos)
Input Voltage (VR1-R2), Typical	2V rms
Input Frequency, Typical	2,5kHz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±10 arcmin
Pairs of Pole	1
Maximum Rational Speed	10,000 rpm
Weight	Approx. 120g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Measuring angular position of cockpit controls (lever, stick and pedal)



### MEAS Synchro

Package	Input Shaft, Integrated Bearing, Size 11
Range	360 degrees absolute
Output	Analog (3 phase)
Input Voltage (VR1-R2), Typical	21V rms - 26V rms
Input Frequency, Typical	400Hz - 2500Hz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±5 arcmin to ±10 arcmin
Pairs of Pole	1
Maximum Rational Speed	10,000 rpm
Weight	Approx. 150g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Angular position of cockpit controls (lever, stick and pedal)



### MEAS Multiturn Position Sensor Unit

Package	Input Shaft, Integrated Bearing, Customized [1]
Range	Multiturn (50.400 to 129.600) degree
Output	2 x Analog (3 phase), Redundant
Input Voltage (VR1-R2), Typical	21V rms - 26V rms
Input Frequency, Typical	400Hz - 2500Hz
Operating Temperature	-55°C to 90°C
Angular Error Rang, Typical	±80 arcmin (400Hz) / ±25 arcmin (2.500Hz)
Pairs of Pole	1
Maximum Rational Speed	600 rpm
Weight	Approx. 935g [1]
Unique Feature	Robust, DO160 qualified
Typical Apps	Multiturn position of primary and secondary flight control actuators



## POSITION SENSORS

Potentiometers, Angular Position Sensors



**MEAS 6000 Series**  
Servo Mount

**Package**

- 12.7 mm - 50.8 mm / .500 in - 2.00 in housing diameter
- 3.170mm - 6.34mm / .1248 in - .2498 in shaft diameter
- 12.7mm - 1.74mm / .500 in - .680 in housing length
- 11.1mm - 47.62mm / .438 in - 1.875 in mounting pilot diameter

**Resistance**

1K - 20K

**Range**

Up to 355 degrees

**Linearity**

± 0.5%

**Output Smoothness**

<0.1%

**Resolution**

Infinite

**Operating Temp**

-65°C to 125°C

**Rotational Life**

50 million cycles min.

**Typical Apps**

Flight control actuators, missile fin actuators



**MEAS 6200 Series**  
Bushing Mount

- 12.7 mm - 50.8 mm / .500 in - 2.00 in housing diameter
- 3.170mm - 6.34mm / .1248 in - .2498 in shaft diameter
- 12.7mm - 1.74mm / .500 in - .680 in housing length
- 3/8 32 NEF thread / 10.31mm / .4062 in pilot diameter

1K - 20K

Up to 355 degrees

± 0.5%

<0.1%

Infinite

-65°C to 125°C

50 million cycles min.

Rocket engine fuel valves, brake pedals



**MEAS 6900 Series**  
Element/Wiper/Insul

- 17.81 mm - 45.85mm / .702 in - 1.805 in element outside diameter
- 4.724 mm - 11.05mm / .186 in - .435 in element inside diameter
- 3.175 mm - 6.35 mm / .125 in - .250 shaft insulator inside diameter
- 4.064 mm - 7.80mm / .160 in - .307 in mating wiper inside diameter
- 5.08 mm / .200 in assembled package height

1K / 5K / 10K

Up to 355 degrees

± 0.5%

< 0.1%

Infinite

-65°C to 125°C

50 million cycles min.

Cargo handling systems, cockpit controls



**MEAS 6100 Series**  
Hollow Shaft

- 27.94 mm - 66.5 mm / 1.100 in - 2.62 in housing diameter
- 3.175 mm - 19 mm / .125 in - .752 in hollow shaft diameter

1K - 20 K

Up to 355 degrees

± 0.5%

< 0.1%

Infinite

-65°C to 125°C

50 million cycles min.

Targeting pod gimbals, missile thrust diverters

## Linear Position Transducers Cable Extension Transducers



**MEAS M150, MTA**

**Range**

0 - 1.5 to 0 - 5 inches

**Output**

Voltage divider

**Environment/  
IP Rating**

IP50

**Enclosure**

Aluminum

**Accuracy**

±0.4% to ±1%

**Unique Features**

- M150, one of the world's smallest stringpot
- Designed for space-critical and testing applications

**Operating Temp**

-40°C to 85°C (M150)  
-55°C to 100°C (MTA)

**Dimensions (mm)**

19 x 19 x 10 (M150)

**Typical Apps**

Aerospace



**MEAS MT2, MT3**

0 - 3 to 0 - 30 inches

Voltage divider, incremental encoder

IP50, IP67 (MT3A)

Aluminum and polycarbonate

±0.25% to ±1.1%

- Designed for test applications
- Dual-axis measuring cable alignment
- Tracks high-acceleration linear position up to 136g's
- High-frequency response
- GAM EG 13 certification

-55°C to 125°C

55 x 45 x 55

Aerospace and flight testing

## Potentiometers, Linear Position Sensors



**MEAS 5903 / 5905 Series**  
Linear Motion

**Package**

- 7.94 mm - 12.7 mm / .312 in - .500 in housing diameter
- 1.98 mm - 3.18 mm / .078 in - .125 in shaft diameter

**Resistance**

1K / 5K / 10K

**Range**

5903 series - up to 50.8 mm / 2 in stroke  
5905 series - up to 101.6 mm / 4 in stroke

**Linearity**

±1%

**Output Smoothness**

<0.1%

**Resolution**

Infinite

**Operating Temp.**

-65°C to 125°C

**Rotational Life**

50 million cycles min

**Typical Apps**

Flight control actuators, targeting pod gimbals, nose wheel position

## POSITION SENSORS

Linear Position Transducers,  
Inductive Absolute



### MEAS M12

<b>Package</b>	AISI-304 Series Stainless steel
<b>Linearity</b>	±0.25% of range
<b>Excitation</b>	AC operated
<b>Output</b>	AC voltage
<b>Range</b>	±10 to ±100 mm
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Metric series</li> <li>• High stroke to length ratio</li> <li>• Constant sum of secondaries</li> <li>• Excellent temperature coefficient</li> </ul>
<b>Operating Temp</b>	-55°C to 150°C (220°C optional)
<b>Diameter (mm)</b>	12
<b>Typical Apps</b>	Hydraulic spool valve position feedback, flight simulators, engine thrust reversers

Angular Position Sensors,  
Hall Effect Absolute



### MEAS H005 / H009 Series

<b>Package</b>	<ul style="list-style-type: none"> <li>• 12.7 mm - 22.19 mm / .500 in - .875 in housing diameter</li> <li>• 3.170 mm / .1248 in shaft diameter</li> <li>• 16.9 mm - 17.4 mm / .670 in - .680 in housing length</li> </ul>
<b>Range</b>	Up to 359 degrees
<b>Output Options</b>	Analog / PWM / Serial
<b>Resolution</b>	12 Bit - Analog / PWM 14 Bit - Serial
<b>Linearity</b>	± 0.2%
<b>Nominal Supply</b>	5 volts
<b>Operating Temp</b>	-40°C to 150°C
<b>Rotational Life</b>	> 100 million cycles (bearing life)
<b>Typical Apps</b>	Missile fin actuation

### MEAS H009-1200 Series Dual Output

<b>Package</b>	<ul style="list-style-type: none"> <li>• 22.23 mm / .875 in housing diameter</li> <li>• 3.170 mm / .1248 in shaft diameter</li> <li>• 26.1 mm / 1.03 in housing length</li> </ul>
<b>Range</b>	Up to 359 degrees (dual output)
<b>Output Options</b>	Analog / PWM / Serial
<b>Resolution</b>	12 Bit - Analog / PWM 14 Bit - Serial
<b>Linearity</b>	± 0.2% (dual output)
<b>Nominal Supply</b>	5 volts (dual output)
<b>Operating Temp</b>	-40°C to 150°C
<b>Rotational Life</b>	> 100 million cycles (bearing life)
<b>Typical Apps</b>	Missile fin actuation

## VIBRATION SENSORS

DC Accelerometers



### MEAS 3038

<b>Package</b>	SMD
<b>Type</b>	MEMS, Board level
<b>F.S. Range (g)</b>	±50, 100, 200, 500, 2000, 6000
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Hermetically sealed</li> <li>• High over-range protection</li> <li>• Gas damping</li> </ul>
<b>Accuracy</b>	±0.5% Non-linearity
<b>Excitation Voltage</b>	—
<b>Operating Temp</b>	-54°C to 125°C
<b>Dimensions (mm)</b>	7.62 x 7.62 x 3.3
<b>Typical Apps</b>	Vibration / shock monitoring, embedded systems, shock testing, safe and arm



### MEAS EGAXT

<b>Package</b>	Stainless steel
<b>Type</b>	Plug and Play, Unamplified, Adhesive / Screw mount
<b>F.S. Range (g)</b>	±5 through 2500
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Sub-miniature</li> <li>• Lightweight</li> <li>• 10,000 g over-range protection</li> </ul>
<b>Accuracy</b>	±1.0% Non-linearity
<b>Excitation Voltage</b>	—
<b>Operating Temp</b>	-40°C to 120°C
<b>Dimensions (mm)</b>	7.2 x 4.6 x 4.6
<b>Typical Apps</b>	Flight test and control, launch, crash, impact testing, robotics



### MEAS 4602/4604HT

<b>Package</b>	Anodized aluminum
<b>Type</b>	Plug and Play, Amplified, Screw mount
<b>F.S. Range (g)</b>	±2, 10, 30, 50, 100, 200, 500
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Exceptional temp compensation</li> <li>• HT version to 170°C</li> <li>• High over-range</li> <li>• Hermetically sealed</li> </ul>
<b>Accuracy</b>	±1.0% Non-linearity
<b>Excitation Voltage</b>	8 - 36 Vdc / 8 - 18 Vdc (HT)
<b>Operating Temp</b>	-54°C to 170°C (HT)
<b>Dimensions (mm)</b>	21.08 x 21.59 x 7.62
<b>Typical Apps</b>	Flight testing on engines, flutter test, weapons development

## VIBRATION SENSORS

DC Accelerometers  
Plug and Play



**MEAS 3420XA**

<b>Package</b>	Anodized aluminum
<b>Type</b>	±1 to 500
<b>F.S. Range (g)</b>	Triaxial
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Analog output</li> <li>• Precision aligned</li> <li>• Performance over temperature</li> </ul>
<b>Accuracy</b>	±0.2% Non-linearity
<b>Excitation Voltage</b>	8.5 to 36 VDC
<b>Operating Temp</b>	-40°C to 85°C
<b>Dimensions (mm)</b>	24 x 24 x 28.30
<b>Typical Apps</b>	Safety system, military research and development



**MEAS 3520XA**

<b>Package</b>	Anodized aluminum
<b>Type</b>	±1 to 500
<b>F.S. Range (g)</b>	1, 2, or 3
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Digital output</li> <li>• Direct to PC</li> <li>• User configurable settings</li> </ul>
<b>Accuracy</b>	±0.2% Non-linearity
<b>Excitation Voltage</b>	8.5 to 36 VDC
<b>Operating Temp</b>	-40°C to 85°C
<b>Dimensions (mm)</b>	52 x 36.50 x 17.50
<b>Typical Apps</b>	Impact detection, stores separation

Piezoelectric Accelerometers  
Plug and Play



**MEAS 7202A/7204A**


<b>Package</b>	Stainless steel
<b>Type</b>	Voltage mode plug, through hole mount
<b>Sensitivity (mV/g)</b>	100, 10
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Annular shear mode</li> <li>• Integral strain relief</li> <li>• Case isolated, internally shielded</li> <li>• 3-pin connector</li> <li>• +150°C option</li> </ul>
<b>Operating Temp</b>	-55°C to 130°C
<b>Dimensions (mm)</b>	13.34 x 19.05
<b>Typical Apps</b>	HUMS applications, rotor track and balance

## PIEZO FILM SENSORS



**MEAS Piezo Cable**

<b>Package</b>	Shielded coaxial 20 gage piezo cable
<b>Type</b>	Polymer jacketing; armored jacketing
<b>Range</b>	µPa sensitivity
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Continuous lengths to 1km</li> <li>• Shielded construction</li> </ul>
<b>Accuracy</b>	±20% (typical)
<b>Operating Temp</b>	-40°C to 85°C (up to 100°C available)
<b>Dimensions (mm)</b>	3 mm diameter; continuous lengths
<b>Typical Apps</b>	Geophone, impact sensors, intrusion detection



**MEAS Tamper Box**

<b>Package</b>	Flat film or box mounted
<b>Type</b>	Tamper detection sensor
<b>Range</b>	Application dependent
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• Low power</li> <li>• Custom shapes and sizes</li> <li>• High security</li> </ul>
<b>Accuracy</b>	Application dependent
<b>Operating Temp</b>	-40°C to 85°C
<b>Dimensions (mm)</b>	Application dependent
<b>Typical Apps</b>	Encryption modules, POS card readers, PIN entry devices, tamper

## ULTRASONIC SENSORS

Standard Contact Point Level



**MEAS LL-01**

<b>Type</b>	Gap
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• All 316L SS</li> <li>• Integral electronics</li> <li>• Miniature threads</li> <li>• Single machined</li> <li>• No adjustment for viscosity, density</li> </ul>
<b>Input</b>	6 - 24VDC
<b>Output</b>	1/2A contact
<b>Pressure</b>	250 psi
<b>Temperature</b>	100°C
<b>Actuation point</b>	0.25"
<b>Process Connection</b>	1/4"NPT & 1/2"NPT
<b>Cable</b>	12"
<b>Approvals</b>	CE
<b>Typical Apps</b>	Compressors, coolant reservoirs



**MEAS LL-10**

<b>Type</b>	Tip
<b>Unique Features</b>	<ul style="list-style-type: none"> <li>• All 316L SS</li> <li>• Integral electronics</li> <li>• No adjustment for viscosity, density</li> </ul>
<b>Input</b>	9 - 24VDC
<b>Output</b>	1A SPDT
<b>Pressure</b>	1000 psi
<b>Temperature</b>	100°C
<b>Actuation point</b>	2.25" standard
<b>Process Connection</b>	3/4"NPT
<b>Cable</b>	12"
<b>Approvals</b>	CE
<b>Typical Apps</b>	Hydraulic reservoirs, dark water

PRODUCT AND APPLICATION MATRIX	Flow	Fluid Property	Force/Torque	Humidity	Liquid Level	Rate/Inertial	Position	Pressure	Temperature	Ultrasonic	Vibration/Shock
	Cockpit Controls			●				●			
Flight Controls and Actuation			●				●				
Landing Gear & Brakes			●				●	●			
Cabin, Galley & Cargo				●	●		●	●	●	●	
Launch & Space			●				●	●	●		●
Engine, Turbine & APU	●				●		●	●	●		●
Military (Missile, Ground Vehicle, Marine, UAV...)	●	●			●	●	●	●	●	●	●

**te.com/aerospacedefense-sensorsolutions**

© 2016 TE Connectivity. All Rights Reserved.

Microfused, UltraStable, Measurement Specialties, MEAS, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this brochure are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

SS-TS-AD200 08/2016

**TE CONNECTIVITY**

For More Information Contact TE

**te.com/sensorsolutions-contact**

**www.te.com**

