


CES-B16-SFFS-PLBK

Order No.: 0801659

<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=0801659>

Sealing frame with screw locking, size B16, with flat gasket, for 8 small sleeves

Commercial data

EAN	 4 046356 674133
sales group	B240
Pack	1 Pcs.
Customs tariff	85472000
Gross weight in pieces	0.1469 KG
Net weight per piece	0.1469 KG

Product notesWEEE/RoHS-compliant since:
06/27/2011

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General data**

Material	PA
Inflammability class according to UL 94	V0
Color	black
Length	120 mm
Degree of protection	IP55

Ambient temperature (operation)	-40 °C ... 120 °C
Torque	2 Nm ... 4 Nm (Locking screw)
Installation instructions	M5 locking screw with 4 mm Allen screw head, 2 ... 4 Nm torque, one large sleeve requires the space of 4 small sleeves.

Certificates / Approvals


Certification
 Certifications applied for:
 Certification Ex:

Accessories


Item	Designation	Description
General		
0801726	CES-B16-WRG-BK	Flat gasket made of NBR, size B16
0801728	CES-SFFS-H	M4 replacement screw with 4 mm Allen screw head for sealing frame with screw locking
1212647	SF-BIT-HEX 3-50	Screw bit, hexagon, E6.3-1/4" drive, size: Hex 3 x 50 mm, hardened, suitable for holder according to DIN 3126-F6.3/ISO 1173
Tools		
1212070	SF-M BH	Bit screwdriver, with 1/4" quick-action chuck, handle length 119 mm, 2-component handle, with non-slip grip, suitable for bits according to DIN 3126-C 6.3 and E 6.3/ISO 1173, magnetic

Drawings

Dimensioned drawing



Dimensional drawing



Panel cutout

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2012 Phoenix Contact
Technical modifications reserved;