

## Flat-ribbon conductor - VS-ASI-FC-TPE-UL-BK 100M - 1404935

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-Interface TPE flat conductor with UL in black, for additional power supply, 2 x 1.5 mm<sup>2</sup>, 100 m ring

### Product Features



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	6550.0 GRM
Custom tariff number	85444995
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Number of positions	2
Shielded	No
Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm <sup>2</sup>
Duty cycle testing	Flexible cable conduit capable
Length of cable	100 m

#### Ambient conditions

Ambient temperature (operation)	-30 °C ... 105 °C (Flexibly installed)
	-40 °C ... 105 °C (fixed routing)
Ambient temperature (assembly)	-30 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C

#### Material data

## Flat-ribbon conductor - VS-ASI-FC-TPE-UL-BK 100M - 1404935

### Technical data

#### Material data

Outer sheath, material	TPE
External sheath, color	Black RAL 9005

#### Electrical characteristics

Rated voltage (III/3)	300 V
Rated surge voltage	2 kV

#### Line characteristics

Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm <sup>2</sup>
Conductor cross section	1.5 mm <sup>2</sup>
AWG power supply	16
Conductor structure, voltage supply	84x 0.15 mm
Core diameter including insulation	2.5 mm
Thickness, insulation	approx. 0.5 mm
Wire colors	brown, blue
External sheath, color	Black RAL 9005
Insulation resistance	≥ 1 MΩ*km
Conductor resistance	≤ 13.7 Ω/km
Nominal voltage, cable	300 V
Test voltage, cable	2000 V
Outer sheath, material	TPE
Material conductor insulation	TPE
Conductor material	Bare Cu litz wires
Cable weight	64 kg/km
Smallest bending radius, fixed installation	≥ 6 mm (one-time)
Traversing direction	horizontal, above the broadside
Max. bending cycles	8000000
Bending radius	75 mm
Traversing rate	4 m/s
Acceleration	4 m/s <sup>2</sup>
Traversing direction	vertical, above the broadside
Max. bending cycles	10000000
Bending radius	50 mm
Special properties	UL-Style 2103
	CSA-File LL55255-42
Flame resistance	UL 1581, Sec. 1061 (Cable Flame)
	IEC 60332-1-2

## Flat-ribbon conductor - VS-ASI-FC-TPE-UL-BK 100M - 1404935

### Technical data

#### Line characteristics

Resistance to oil	UL 1581, Sec. 480 (60°C)
Other resistance	UV resistant

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27062002
eCl@ss 5.1	27062002
eCl@ss 6.0	27062002
eCl@ss 7.0	27062002
eCl@ss 8.0	27061801

#### ETIM

ETIM 3.0	EC000825
ETIM 4.0	EC000825
ETIM 5.0	EC000830

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501