


Coding Spline  
 Working Temp: 125°C  
 Color: Red  
 Body: PA66/6 UL94-Vo  
 Application: Plug-in Connectors




**POL-P**


| Cat. # | Length (mm) | Std. Pk. |
|--------|-------------|----------|
| POL-P  | 7.90        | 30/5     |

**Used for parts:**

- PVXX-5.00, 5.08, 7.50
- PHXX-5.00, 5.08, 7.50
- PVPXX-5.00, 5.08, 7.50
- PHPXX-5.00, 5.08, 7.50
- PDSHXX-5.00, 5.08
- PDSVXX-5.00, 5.08
- PDVXX-5.00, 5.08
- PDHXX-5.00, 5.08
- PIXX-5.00, 5.08
- PIPXX-5.00, 5.08
- SFXX-5.00, 5.08



Coding Spline  
 Working Temp: 125°C  
 Color: Red  
 Body: PA66/6 UL94-Vo  
 Application: Plug-in Connectors




**POL-S**


| Cat. # | Length (mm) | Std. Pk. |
|--------|-------------|----------|
| POL-S  | 7.90        | 30/5     |

**Used for parts:**

- SHXX-5.00, 5.08, 7.50
- PVPXX-3.50, 3.81
- PHPXX-3.50, 3.81
- SVFXX-5.08
- SVP-5.08




Jumpers, Adjacent  
 Working Temp: 125°C  
 Color: Green  
 Body: PA66/6 UL94-Vo  
 Application: Jumper Connection  
 Design: 5.08 Spacing Modular




**PT5**

| Cat. # | Length (B) (mm) | Std. Pk. |
|--------|-----------------|----------|
| PT5    | 10.16           | 100      |



Jumpers, Alternate  
 Working Temp: 125°C  
 Color: Green  
 Body: PA66/6 UL94-Vo  
 Application: Jumper Connection  
 Design: 10.16 Spacing Modular



**PT10**

| Cat. # | Length (B) (mm) | Std. Pk. |
|--------|-----------------|----------|
| PT10   | 10.16           | 100      |

