

Fiber Optic Cable

Introduction

Use these zipcord dual fiber optic cables to make your fiber optic connections. Fiber optic cable assemblies are ideal for noisy applications where voltage transients can affect communication. These fiber optic cables are made of durable insulation and come fitted with ST connectors which makes for a quick setup and operation. Custom length plenum rated fiber optic cables with ST connectors can also be ordered. Cables work with all of B&B Electronics fiber optic equipment. See list of part numbers below for pre-made standard lengths of cable.



B&B Part Number	Description
FOP1MST.....	1 meter ST/ST duplex 62.5/125 Cable Assembly
FOP3MST.....	3 meter ST/ST duplex 62.5/125 Cable Assembly
FOP5MST.....	5 meter ST/ST duplex 62.5/125 Cable Assembly
FOP10MST.....	10 meter ST/ST duplex 62.5/125 Cable Assembly
FOPSTC.....	Custom Length Plenum-Rated Simplex Cable Terminated with ST Connectors

Specifications

Fiber Type.....Multimode (graded index)
 Fiber Size.....2.5/125
 Maximum Attenuation (1310/1550nm)3.5/1.2 dB/km
 Typical Attenuation (1310/1550nm)3.0/1.0 dB/km
 Bandwidth in MHz/km (850nm/1300nm)160/500
 Operating Temperature:
 Riser Rated-4°F to 122°F (-20°C to +50°C)
 Plenum Rated+32°F to 122°F (0°C to +50°C)
 Size.....0.11in x 0.29 in (2.90mm x 6.0mm)
 Weight10lbs/1000 feet (15kg/km)

B&B Electronics -- October 1997

B&B Electronics Mfg. Co.
 707 Dayton Road - P.O. Box 1040 - Ottawa, IL 61350 USA
 Phone: (815) 433-5100 - Fax: (815) 434-5105
 Home Page: www.bb-elec.com
 Sales e-mail: sales@bb-elec.com - Fax: (815) 433-5109
 Technical Support e-mail: support@bb-elec.com - Fax: (815) 433-5104

B&B Electronics Ltd
 Westlink Commercial Park - Oranmore, Co. Galway - Ireland
 Phone: (353) 91 792444 - Fax: (353) 91 792445
 Home Page: www.bb-europe.com
 Sales e-mail: sales@bb-europe.com
 Technical Support e-mail: support@bb-europe.com