

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	INITAIL	19SEP2017	YC	CW

- NOTES:
1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 500V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.14~4.0 mm² (26~12 AWG)
CONTACT TYPE: CRIMP CONTACT
2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20300X20XX000)

- 注释:
1. 技术参数:
绝缘材料: PC
额定电压: 500V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 6KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.14~4.0 mm² (26~12 AWG)
接线类型: 冷压接
2. 端子需要单独订购.
(订货号参考图面: T20300X20XX000)

T2111202201-007		HMN-020-F		HMN-020 FEMALE MODULE INSERT HMN-020模块母插	
PART NUMBER 料 号		PART DESCRIPTION 描 述			
DWN 19SEP2017 YORK CHEN		TE Connectivity NAME HMN-020-F			
CHK 19SEP2017 GINO YAO					
APVD 19SEP2017 CHRIS WANG					
PRODUCT SPEC 108-137063					
APPLICATION SPEC 114-137063		SIZE		CAGE CODE	
WEIGHT -		A3		00779	
CUSTOMER DRAWING		SCALE 1:1		SHEET 1 OF 1	
				REV B	

THIS DRAWING IS A CONTROLLED DOCUMENT.	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC ±-
	1 PLC ±-
	2 PLC ±-
	3 PLC ±-
	4 PLC ±-
MATERIAL -	FINISH -