




Weather Proof your connections with Song Chuan's new Weatherproof Sockets Easy Push-to-seat terminals-**with TPA**






SC P/N	Item Description	O.D.	Relay
896WPT	630 - Mini ISO Socket with Seal		896-D1SW
SBWP	Wire Seal - Blank Plug		
S12WP	Wire Seal - 12 AWG GXL	.135" - .154"	
S14WP	Wire Seal - 14-16 AWG GXL	.102" - .134"	
S18WP	Wire Seal - 18-20 AWG GXL	.063" - .094"	
SC Purchase Price			
896WPT	\$1.14 with TPA	@ 10K QTY	
ANY Seals	\$0.08	@ 10K QTY	

SUGGESTED AMP TERMINALS



60253=12-16 AWG - 42100=18 AWG

4/5 PIN WEATHERPROOF AUTOMOTIVE RELAY SOCKET




hole diameter
.314"

[6.3mm load pins
ISO 7588 footprint]





896WPT



SEALS





SBWP



S18WP



S14WP



S12WP



Specifications | Weatherproof Sockets & Seals have been tested to rigorous SAE standards:

Material Specs.: Heat Resistant Nylon - Dupont Zytel 103 FHS

Salt Spray: ASTM B117/SAE1455,

Dust Bombardment: SAE 1455, sect. 4.7


Fluid Compatibility: SAE 1455, sect. 4.4

Temp Range: - 40°C to + 125°C

Compliant to GMW 3191 sect. 4.9: when used with recommended terminals and seals.

Contact us for free sample and trial

Coming Soon



897WPT High Power



2841 Center Port Circle, Pompano Beach, Florida 33064 | 954-788-5889

For use instructions please visit www.songchuanusa.com