

# Series 70

**Characteristics**

The Series 70 consists of special short stroke pushbuttons for use with membrane keyboards. It is particularly suited for:

- PCBs

The use of single LEDs ensures that the entire control panel is very well illuminated. The module is offered in six colours and in a round or square design.

**Functions**

The Series 70 incorporates the following functions:

- Indicator
- Pushbutton
- Illuminated pushbutton

**Market segments**

The EAO Series 70 is especially suited for applications in the segments:

- Machinery and Automation
- Medicinal technology
- Laboratory and measuring equipment

Please refer to the EAO website to obtain detailed information regarding this series [www.products.eao.com](http://www.products.eao.com)  
Configure a product to your exact needs and request a quotation.





|                                        |            |
|----------------------------------------|------------|
| <b>Overview</b>                        |            |
| <b>PCB pushbuttons</b>                 |            |
| Illumination element                   | 680        |
| Switching element without illumination | 681        |
| Switching element with illumination    | 682        |
| <b>Accessories</b>                     | <b>683</b> |
| <b>Drawings</b>                        | <b>687</b> |
| <b>Technical data</b>                  | <b>688</b> |
| <b>Application guidelines</b>          | <b>690</b> |


|           |
|-----------|
| 01        |
| 02        |
| 03        |
| 04        |
| 10        |
| 14        |
| 17        |
| 18        |
| 19        |
| 22        |
| 31        |
| 41        |
| 44        |
| 51        |
| 56        |
| 57        |
| 61        |
| <b>70</b> |
| 71        |
| 82        |
| 84        |
| 92        |
| 95        |
| 96        |
| 97        |
| 99        |
| ST        |

# 70 PCB pushbuttons

## Illumination element



Product can differ from the current configuration.



Dimensions

### Equipment consisting of (schematic overview)



Lens

page 684



LED



Illumination element

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.

### Additional Information

- The customer has to decide what series resistor shall be used to the LED
- Dimensions with fitted lens see details «Lens»
- Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination

| LED colour                                                                                                     | Forward voltage typ. | Lumi. intensity | Dom. wavelength  | Terminal | Part No.          | Component layout | Wiring diagram | Weight   |
|----------------------------------------------------------------------------------------------------------------|----------------------|-----------------|------------------|----------|-------------------|------------------|----------------|----------|
|  <b>Illumination element</b> |                      |                 |                  |          |                   |                  |                |          |
| Single-LED red                                                                                                 | 2.1 VDC @ 20 mA      | 200 mcd         | 625 nm           | PCB      | <b>70-820.2</b>   | 3                | 2              | 0.001 kg |
| Single-LED orange                                                                                              | 2.1 VDC @ 20 mA      | 220 mcd         | 590 nm           | PCB      | <b>70-820.3</b>   | 3                | 2              | 0.001 kg |
| Single-LED yellow                                                                                              | 3.3 VDC @ 30 mA      | 500 mcd         | 570 nm           | PCB      | <b>70-820.4</b>   | 3                | 2              | 0.001 kg |
| Single-LED green                                                                                               | 3.5 VDC @ 20 mA      | 250 mcd         | 525 nm           | PCB      | <b>70-820.5</b>   | 3                | 2              | 0.001 kg |
| Single-LED blue                                                                                                | 3.5 VDC @ 20 mA      | 450 mcd         | 470 nm           | PCB      | <b>70-820.6</b>   | 3                | 2              | 0.001 kg |
| Single-LED white                                                                                               | 3.3 VDC @ 20 mA      | 600 mcd         | x=0.29/y=0.31 nm | PCB      | <b>70-820.9</b>   | 3                | 2              | 0.001 kg |
|  <b>Illumination element</b> |                      |                 |                  |          |                   |                  |                |          |
| Bi-colour red/green                                                                                            | 2.0/3.2 VDC @ 20 mA  | 310/800 mcd     | 625/528 nm       | PCB      | <b>70-820.25</b>  | 3                | 1              | 0.001 kg |
| Bi-colour yellow/green                                                                                         | 2.0/3.2 VDC @ 20 mA  | 350/750 mcd     | 591/528 nm       | PCB      | <b>70-820.45</b>  | 3                | 1              | 0.001 kg |
|  <b>Illumination element</b> |                      |                 |                  |          |                   |                  |                |          |
| without LED                                                                                                    |                      |                 |                  | PCB      | <b>92-800.042</b> | 1                |                | 0.001 kg |

The component layouts you will find from page 687



Switching element without illumination


Equipment consisting of (schematic overview)

**Spacing cap** *page 685*

**Switching element**

Each Part Number listed below includes all the black components shown in the 3D-drawing.

To obtain a complete unit, please select the red components from the pages shown.



Dimensions




Product can differ from the current configuration.

Additional Information

- Contact normally open
- Switching action momentary
- Dimensions with fitted spacing cap see details «Spacing cap»

| Product attribute                                                                                                                    | Contact material | Terminal | Part No. | Component layout | Wiring diagram | Weight   |
|--------------------------------------------------------------------------------------------------------------------------------------|------------------|----------|----------|------------------|----------------|----------|
| <br><b>Switching element without illumination</b> |                  |          |          |                  |                |          |
| without spacing cap                                                                                                                  | Silver           | PCB      | 70-100.0 | 2                | 2              | 0.001 kg |
| <br><b>Switching element without illumination</b> |                  |          |          |                  |                |          |
| with spacing cap                                                                                                                     | Silver           | PCB      | 70-101.0 | 2                | 2              | 0.001 kg |
| <br><b>Switching element without illumination</b> |                  |          |          |                  |                |          |
| with spacing cap                                                                                                                     | Gold             | PCB      | 70-201.0 | 1                | 1              | 0.001 kg |

The component layouts you will find from page 687




# 70 PCB pushbuttons

## Switching element with illumination



Product can differ from the current configuration.



Dimensions

### Equipment consisting of (schematic overview)



Lens

page 684



LED



Switching element

Each Part Number listed below includes all the black components shown in the 3D-drawing.


To obtain a complete unit, please select the red components from the pages shown.

### Additional Information

- Contact normally open
- Switching action momentary
- The customer has to decide what series resistor shall be used to the LED
- Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination
- Dimensions with fitted lens see details «Lens»

| LED colour                                                                                                                    | Forward voltage typ. | Contact material | Lumi. intensity | Dom. wavelength  | Terminal | Part No.          | Component layout | Wiring diagram | Weight   |
|-------------------------------------------------------------------------------------------------------------------------------|----------------------|------------------|-----------------|------------------|----------|-------------------|------------------|----------------|----------|
|  <b>Switching element with illumination</b> |                      |                  |                 |                  |          |                   |                  |                |          |
| Single-LED red                                                                                                                | 2.1 VDC @ 20 mA      | Gold             | 200 mcd         | 625 nm           | PCB      | <b>70-220.2</b>   | 4                | 3              | 0.001 kg |
| Single-LED orange                                                                                                             | 2.1 VDC @ 20 mA      | Gold             | 220 mcd         | 590 nm           | PCB      | <b>70-220.3</b>   | 4                | 3              | 0.001 kg |
| Single-LED yellow                                                                                                             | 3.3 VDC @ 20 mA      | Gold             | 500 mcd         | 570 nm           | PCB      | <b>70-220.4</b>   | 4                | 3              | 0.001 kg |
| Single-LED green                                                                                                              | 3.5 VDC @ 20 mA      | Gold             | 250 mcd         | 525 nm           | PCB      | <b>70-220.5</b>   | 4                | 3              | 0.001 kg |
| Single-LED blue                                                                                                               | 3.5 VDC @ 20 mA      | Gold             | 450 mcd         | 470 nm           | PCB      | <b>70-220.6</b>   | 4                | 3              | 0.001 kg |
| Single-LED white                                                                                                              | 3.3 VDC @ 20 mA      | Gold             | 600 mcd         | x=0.29/y=0.31 nm | PCB      | <b>70-220.9</b>   | 4                | 3              | 0.001 kg |
|  <b>Switching element with illumination</b> |                      |                  |                 |                  |          |                   |                  |                |          |
| Bi-colour LED red/green                                                                                                       | 2.0/3.2 VDC @ 20 mA  | Gold             | 310/800 mcd     | 625/528 nm       | PCB      | <b>70-220.25</b>  | 4                | 2              | 0.001 kg |
| Bi-colour LED yellow/green                                                                                                    | 2.0/3.2 VDC @ 20 mA  | Gold             | 350/750 mcd     | 591/528 nm       | PCB      | <b>70-220.45</b>  | 4                | 2              | 0.001 kg |
|  <b>Switching element with illumination</b> |                      |                  |                 |                  |          |                   |                  |                |          |
| without LED                                                                                                                   |                      | Gold             |                 |                  | PCB      | <b>92-851.342</b> | 4                | 1              | 0.001 kg |

The component layouts you will find from page 687




|           |
|-----------|
| 01        |
| 02        |
| 03        |
| 04        |
| 10        |
| 14        |
| 17        |
| 18        |
| 19        |
| 22        |
| 31        |
| 41        |
| 44        |
| 51        |
| 56        |
| 57        |
| 61        |
| <b>70</b> |
| 71        |
| 82        |
| 84        |
| 92        |
| 95        |
| 96        |
| 97        |
| 99        |
| ST        |

# 70 Accessories

## Front

## Lens




Dimensions

| Lens                                                                                                                                   | Part No. | Weight   |
|----------------------------------------------------------------------------------------------------------------------------------------|----------|----------|
|  <p><b>Lens, Front dimension 19.05 x 19.05 mm</b></p> |          |          |
|                                                                                                                                        | 70-920.9 | 0.001 kg |
|  <p><b>Lens, Front dimension 15.4 x 15.4 mm</b></p> |          |          |
|                                                                                                                                        | 70-921.2 | 0.001 kg |
|                                                                                                                                        | 70-921.3 | 0.001 kg |
|                                                                                                                                        | 70-921.4 | 0.001 kg |
|                                                                                                                                        | 70-921.5 | 0.001 kg |
|                                                                                                                                        | 70-921.6 | 0.001 kg |
|                                                                                                                                        | 70-921.9 | 0.001 kg |
|  <p><b>Lens, Front dimension 12.4 x 12.4 mm</b></p> |          |          |
|                                                                                                                                        | 70-922.2 | 0.001 kg |
|                                                                                                                                        | 70-922.3 | 0.001 kg |
|                                                                                                                                        | 70-922.4 | 0.001 kg |
|                                                                                                                                        | 70-922.5 | 0.001 kg |
|                                                                                                                                        | 70-922.6 | 0.001 kg |
|                                                                                                                                        | 70-922.9 | 0.001 kg |
|  <p><b>Lens, Front dimension Ø 15.4 mm</b></p>       |          |          |
|                                                                                                                                        | 70-911.2 | 0.001 kg |
|                                                                                                                                        | 70-911.3 | 0.001 kg |
|                                                                                                                                        | 70-911.4 | 0.001 kg |
|                                                                                                                                        | 70-911.5 | 0.001 kg |
|                                                                                                                                        | 70-911.9 | 0.001 kg |

| Lens                                                                                                                     | Part No.        | Weight   |
|--------------------------------------------------------------------------------------------------------------------------|-----------------|----------|
|  <b>Lens, Front dimension Ø 12.4 mm</b> |                 |          |
| Plastic red translucent                                                                                                  | <b>70-912.2</b> | 0.001 kg |
| Plastic orange translucent                                                                                               | <b>70-912.3</b> | 0.001 kg |
| Plastic yellow translucent                                                                                               | <b>70-912.4</b> | 0.001 kg |
| Plastic green translucent                                                                                                | <b>70-912.5</b> | 0.001 kg |
| Plastic white translucent                                                                                                | <b>70-912.9</b> | 0.001 kg |

### Spacing cap



Dimensions

| Product attribute                                                                                      | Part No.        | Weight   |
|--------------------------------------------------------------------------------------------------------|-----------------|----------|
|  <b>Spacing cap</b> |                 |          |
| without recesses for LED, H = 18.9 mm                                                                  | <b>70-901.0</b> | 0.001 kg |
| 2 recesses for LED, H = 9 mm                                                                           | <b>70-910.0</b> | 0.001 kg |
| 2 recesses for LED, H = 13 mm                                                                          | <b>70-911.0</b> | 0.001 kg |
| 2 recesses for LED, H = 22.5 mm                                                                        | <b>70-912.0</b> | 0.001 kg |

## Illumination

### Single-LED, T1 Bi-Pin

#### Additional Information

- The customer has to decide what series resistor shall be used to the LED
- Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination

| LED colour                                                                                         | Forward voltage typ. | Lumi. intensity | Dom. wavelength  | Part No.             | Weight   |
|----------------------------------------------------------------------------------------------------|----------------------|-----------------|------------------|----------------------|----------|
|  <b>Single-LED</b> |                      |                 |                  |                      |          |
| Single-LED red                                                                                     | 2.1 VDC @ 20 mA      | 200 mcd         | 625 nm           | <b>10-2602.3202L</b> | 0.001 kg |
| Single-LED orange                                                                                  | 2.1 VDC @ 20 mA      | 220 mcd         | 590 nm           | <b>10-2602.3203L</b> | 0.001 kg |
| Single-LED yellow                                                                                  | 3.3 VDC @ 20 mA      | 500 mcd         | 570 nm           | <b>10-2602.3204L</b> | 0.001 kg |
| Single-LED green                                                                                   | 3.5 VDC @ 20 mA      | 250 mcd         | 525 nm           | <b>10-2602.3205L</b> | 0.001 kg |
| Single-LED blue                                                                                    | 3.5 VDC @ 20 mA      | 450 mcd         | 470 nm           | <b>10-2602.3206L</b> | 0.001 kg |
| Single-LED white                                                                                   | 3.3 VDC @ 20 mA      | 600 mcd         | x=0.29/y=0.31 nm | <b>10-2602.3209L</b> | 0.001 kg |


### Bi-colour-LED, T1 Bi-Pin

#### Additional Information

- The customer has to decide what series resistor shall be used to the LED
- Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination

| LED colour                                                                                              | Forward voltage typ. | Lumi. intensity | Dom. wavelength | Part No.             | Weight   |
|---------------------------------------------------------------------------------------------------------|----------------------|-----------------|-----------------|----------------------|----------|
|  <b>Bi-colour-LED</b> |                      |                 |                 |                      |          |
| Bi-colour LED red/green                                                                                 | 2.0/3.2 VDC @ 20 mA  | 310/800 mcd     | 625/528 nm      | <b>10-2603.308AL</b> | 0.001 kg |
| Bi-colour LED yellow/green                                                                              | 2.0/3.2 VDC @ 20 mA  | 350/750 mcd     | 591/528 nm      | <b>10-2603.308CL</b> | 0.001 kg |


## Drawings



### Single-LED

Drilling plan (element side)

- B Holes for LED
- C Holes for centering pins




Component layout 3

### Bi-colour-LED

Drilling plan (element side)


- B Holes for Bi-colour LED:  
BA1 (green) + BA2 (yellow or red) = Anodes, BC = Cathode
- C Holes for centering pins



### Single-LED

Drilling plan (element side)

- B Holes for LED
- C Holes for contact pins  
Pad max.  $\varnothing 2.5$  mm  
Through-connection recommended




Component layout 4

### Bi-colour-LED

Drilling plan (element side)

- B Holes for Bi-colour-LED:  
BA1 (green) + BA2 (yellow or red) = Anodes, BK = Cathode
- C Holes for contact pins  
Pad max.  $\varnothing 2.5$  mm  
Through-connection recommended



# 70 Technical data

## Switching element illuminated

### Switching system

Short-travel switching system with two independent contact points and tactile operation. Guarantees reliable switching even of very light loads.

1 normally open contact

### Material

#### Material of contact

Gold (Au)

#### Switching element

Thermoplastic Polyester (PET, PBT) and Polyacetale (POM)

### Mechanical characteristics

#### Actuating force

with overlay foil 4 N  $\pm$  1,5 N

Max. actuating force > 50 N, as per DIN 42115

#### Actuating travel

0.4 mm

#### Rebound time

$\leq$  1 ms

#### Resistance to heat of soldering

260 °C, 5 s, as per IEC 60068-2-20

#### Mechanical lifetime

> 5 million operations

### Electrical characteristics

#### Contact resistance

Starting value (initial)  $\leq$  100 m $\Omega$ , as per IEC 60512-2-2b

#### Isolation resistance

$\geq$  1000 M $\Omega$

#### Contact resistance

$\leq$  100 m $\Omega$

as per 500 000 cycles of operation at 12 VDC, 5 mA resistive load  $\leq$  200 m $\Omega$

#### Electrical life

$\geq$  500 000 operations at 42 VDC, 50 mA, as per IEC 60512-5-9c

When attention is paid to the direction of current flow from terminal 3/4 to 1/2 the electrical life can be prolonged.

#### Switch rating

max. 2 VA (resistive load)

#### Switch rating

|                           |                 |             |
|---------------------------|-----------------|-------------|
| Switching voltage VDC/VAC | min. 50 mV      | max. 42 V   |
| Switching current VDC/VAC | min. 10 $\mu$ A | max. 100 mA |
| Power rating              | max. 2 W        |             |

#### Electric strength

500 VAC, 50 Hz, 1 min, as per IEC 60512-2-4a

### Environmental conditions

#### Storage temperature

-40 °C ... +85 °C

#### Operating temperature

-25 °C ... +70 °C

## Switching element non-illuminated Part No. 70-100.0 and 70-101.0

### Switching system

Short-travel switching system with two independent contact points and tactile operation. Guarantees reliable switching even of very light loads.

1 normally open contact

### Material

#### Material of contact

Silver (Ag)

### Mechanical characteristics

#### Actuating force

with overlay foil 5 N  $\pm$  2 N

Max. actuating force > 50 N, as per DIN 42115

#### Actuating travel

0.3 mm

#### Rebound time

$\leq$  5ms

#### Mechanical lifetime

> 1 million operations

## Electrical characteristics

### Isolation resistance

≥ 50 MΩ

### Contact resistance

≤ 100 mΩ

as per 500 000 cycles of operation at 12 VDC, 5 mA resistive load ≤ 200 mΩ

### Electrical life

at 5 VDC, 1 mA > 1 million operations

at 24 VDC, 1 mA > 100 000 operations

### Switch rating

≤ 1 VA (resistive load)

### Switch rating

≤ 24 VDC, ≤ 50 mA

### Electric strength

250 VAC for 1 min.

## Environmental conditions

### Storage temperature

-30 °C ... +85 °C

### Operating temperature

-20 °C ... +70 °C

## Switching element non-illuminated Part No. 70-201.0

## Switching system

Short-travel switching system with two independent contact points and tactile operation. Guarantees reliable switching even of very light loads.

1 normally open contact

## Material

### Material of contact

Gold (Au)

### Switching element

Thermoplastic Polyester (PET, PBT) and Polyacetale (POM)

## Mechanical characteristics

### Actuating force

with overlay foil 2.1 N ±0.2 N

Max. actuating force > 50 N, as per DIN 42115

### Actuating travel

max. 0.5 mm

### Rebound time

≤ 1 ms

### Resistance to heat of soldering

260 °C, 5 s, as per IEC 60068-2-20

### Mechanical lifetime

> 5 million operations

### Front protection

front with overlay foil IP 65

## Electrical characteristics

### Contact resistance

Starting value (initial) ≤ 100 mΩ, as per IEC 60512-2-2b

### Isolation resistance

≥ 1000 MΩ

### Contact resistance

≤ 100 mΩ

as per 500 000 cycles of operation at 12 VDC, 5 mA resistive load ≤ 200 mΩ

### Electrical life

≥ 500 000 operations at 42 VDC, 50 mA, as per IEC 60512-5-9c

When attention is paid to the direction of current flow from terminal ¾ to ½ the electrical life can be prolonged.

### Switch rating

max. 42 V, 50 mA

min. 50 mV, 10 µA

### Switch rating

|                           |            |             |
|---------------------------|------------|-------------|
| Switching voltage VDC/VAC | min. 50 mV | max. 42 V   |
| Switching current VDC/VAC | min. 10 mA | max. 100 mA |
| Switch rating             | max. 2 W   |             |

### Electric strength

500 VAC, 50 Hz, 1 min, as per IEC 60512-2-4a

## Environmental conditions

### Storage temperature

-40 °C ... +85 °C

### Operating temperature

-25 °C ... +70 °C

EAO reserves the right to alter specifications without further notice.

# 70 Application guidelines

## Suppressor circuits


When switching inductive loads such as relays, DC motors, and DC solenoids, it is always important to absorb surges (e.g. with a diode) to protect the contacts. When these inductive loads are switched off, a counter emf can severely damage switch contacts and greatly shorten lifetime.

Fig. 1 shows an inductive load with a free-wheeling diode connected in parallel. This free-wheeling diode provides a path for the inductor current to flow when the current is interrupted by the switch. Without this free-wheeling diode, the voltage across the coil will be limited only by dielectric breakdown voltages of the circuit or parasitic elements of the coil. This voltage can be kilovolts in amplitude even when nominal circuit voltages are low (e.g. 12VDC) see Fig. 2.

The free-wheeling diode should be chosen so that the reverse breakdown voltage is greater than the voltage driving the inductive load. The DC blocking voltage ( $V_R$ ) of the free-wheeling diode can be found in the datasheet of a diode. The forward current should be equal or greater than the maximum current flowing through the load.

**To get an efficient protection, the free-wheeling diode must be connected as close as possible to the inductive load!**

Switching with inductive load  
Fig. 1



Counter EMF  
over load without free-wheeling diode  
Fig. 2

