

## ZFKKDSA 1,5-5,08- 4 MIXBDNZ04 - 1706481

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block, nominal current: 12 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 4, connection method: Spring-cage connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: multi-color

The figure shows an 10-position version

#### Your advantages

- ☑ Defined contact force ensures that contact remains stable over the long term
- ☐ Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- Conductor connection on several levels enables higher contact density
- The latching on the side enables various numbers of positions to be combined



#### **Key Commercial Data**

Packing unit	50 pc	
GTIN	4 046356 862363	
GTIN	4046356862363	

## Technical data

#### Dimensions

Length [1]	24 mm
Pitch	5.08 mm
Dimension a	15.24 mm
Width [w]	21.32 mm
Height	25.5 mm
Height [ h ]	29 mm
Solder pin [P]	3.5 mm
Hole diameter	1.3 mm

#### General

Range of articles	ZFKKDS(A) 1,5
Rated surge voltage (III/3)	4 kV



## ZFKKDSA 1,5-5,08- 4 MIXBDNZ04 - 1706481

## Technical data

## General

Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV
Rated voltage (III/3)	250 V
Rated voltage (III/2)	400 V
Rated voltage (II/2)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	12 A
Nominal cross section	1.5 mm²
Internal cylindrical gage	A1
Stripping length	7.5 mm
Number of positions	4

#### Connection data

Conductor cross section AWG min.	24
Conductor cross section AWG max.	14

## Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

## **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

## **Approvals**

#### Approvals

Approvals

EAC / cULus Recognized

Ex Approvals

## Approval details

EAC ENC



# ZFKKDSA 1,5-5,08- 4 MIXBDNZ04 - 1706481

## Approvals

cULus Recognized <b>CFL</b> US	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-19941110	
	D	В
Nominal voltage UN	300 V	250 V
Nominal current IN	10 A	10 A
mm²/AWG/kcmil	26-12	26-12

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com