





LOC	DIST	REVISIONS						
		P	LTR	DESCRIPTION	DATE	DWN	APVD	
ES	00		G9	ADD NEW DASH NUMBER 2-9	04MAY2012	CZ	SZ	
			H2	REV PER ECR-12-020199	22NOV2012	CZ	SZ	
			H4	ADDED THE NEW DASH NUMBER -33	28DEC2012	ML	SZ	



- 1 "AMP", PART NUMBER, AND DATECODE TO BE MARKED IN AREA SHOWN. PARTS UNDER 2.00 LONG MAY BE MARKED ON BOTH SIDES.
- 2 MATERIAL:
HOUSING - GLASS FILLED HIGH TEMP THERMO PLASTIC,BLACK, UL94 V-0
SIGNAL CONTACT - COPPER ALLOY
POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3 CONTACT PLATING - NOBLE METAL PLATING ON CONTACT FUNCTIONAL AREA OF POWER AND SIGNAL CONTACTS
- 4 MECHANICAL CONNECTOR KEEP OUT ZONE.
- 5 DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 6 PCB - HOLE DIAMETERS ARE FINISHED HOLE SIZE.
- 7 PCB - .0453±.0010 DRILLED HOLES PLATED WITH .0003 MIN Sn OVER .001 TO .003 Cu PLATING TO ACHIEVE A .040 DIA HOLE.
- 8 TO GENERAL POWER CONTACT (WITHOUT LP POWER CONTACT), VARIABLE DIMENSIONS PLEASE SEE SHEET 2.
- 9 PLEASE REFER TO PAGE 5 FOR DETAIL DIMENSIONS.
- 10 PLEASE REFER TO PAGE 7 FOR SPECIAL DIMENSIONS.
- 11 FOR LP/S/P CONFIGURATION, OR SPECIAL DIMENSIONS FOR PART 2-6450840-1, PLEASE REFER TO SHEET 2.



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ALEX SHOAL CHK Sunny Zhao APVD Sunny Zhao	14DEC2007 20DEC2007 20DEC2007	TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-2292 APPLICATION SPEC 114-13251	NAME RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE	
MATERIAL 2		0 PLC ±" 1 PLC ±.01 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0050 ANGLES ±2° FINISH 3	SIZE 100779	CAGE CODE C=6450840	RESTRICTED TO -
Customer Drawing		SCALE 4:1	SHEET 1	OF 16	REV H4

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

.250	2.315	1.535	.860	2.205	.230	2.415	2.555	.1275	6LP + 24S + 3P	3-6450840-3
-	1.135	.8075	.375	1.025	-	1.235	1.375	.1025	2LP + 16S + 2LP	3-6450840-1
.250	2.300	1.520	.845	2.190	.250	2.400	2.540	.170	3P + 24S + 3P	2-6450840-9
.250	3.800	2.270	1.595	3.690	.250	3.900	4.040	.170	6P + 24S + 6P	2-6450840-7
.250	4.400	2.370	2.095	4.290	.250	4.500	4.640	.170	8P + 8S + 8P	1-6450840-6
.250	1.700	1.145	.645	1.590	.250	1.800	1.940	.195	2P + 16S + 2P	2-6450840-5
.250	6.000	3.970	2.095	5.890	.250	6.100	6.240	.170	8P + 72S + 8P	2-6450840-3
.250	2.500	1.470	1.095	2.390	.250	2.600	2.740	.170	4P + 12S + 4P	2-6450840-2
.230	5.585	1.5025	.645	5.475	.250	5.685	5.825	.170	2P + 32S + 4LP + 14P	2-6450840-1
.250	3.520	2.990	2.265	3.410	.230	3.620	3.760	.1525	18LP + 24S + 2P	2-6450840-0
-	1.300	1.020	.345	1.190	-	1.400	1.540	.170	1P + 24S + 1P	1-6450840-5
.200	3.300	2.020	1.345	3.190	.200	3.400	3.540	.170	6HDP + 24S + 6HDP	1-6450840-2
.200	2.400	1.520	.945	2.290	.200	2.500	2.640	.170	4HDP + 20S + 4HDP	1-6450840-1
.250	2.400	1.370	1.095	2.290	.250	2.500	2.640	.170	4P + 8S + 4P	1-6450840-0
.200	2.100	1.220	.945	1.990	.200	2.200	2.340	.170	4HDP + 8S + 4HDP	6450840-9
-	8	-	-	-	-	-	-	-	4P+16S+24S+2HDP	6450840-8
-	1.300	1.020	.345	1.190	-	1.400	1.540	.170	1P + 24S + 1P	6450840-7
-	2.480	2.1525	1.345	2.370	.250	2.580	2.720	.170	5P + 32S + 2LP	6450840-6
.250	3.400	2.120	1.395	3.290	.250	3.500	3.640	.170	5P + 24S + 5P	6450840-5
.200	5.150	2.670	1.345	5.040	.300	5.250	5.390	.195	4ACP + 48S + 12HDP	6450840-4
.230	5.495	4.4275	3.170	5.385	.250	5.595	5.735	.195	12P + 48S + 8LP	6450840-3
-	2.315	-	-	2.205	-	2.415	2.555	.170	3P+ 1LP + 24S + 3HDP	6450840-2
DIM T	DIM V	DIM R	DIM W	DIM U	DIM S	DIM D	DIM L	DIM K	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±.01
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0050
ANGLES ±.2°
FINISH

MATERIAL

-

DWN
CHK
APVD

ALEX SHOAL
Suryy Zhao
Suryy Zhao

14DEC2007
20DEC2007
20DEC2007

NAME

RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A100779

6450840

Customer Drawing

SCALE

1:1

SHEET


2

OF


16

REV


H4



FOR P/S/P CONFIGURATION
UNSPECIFIED DIM REFER TO SHEET 1
SCALE 4:1



FOR LP/S/P CONFIGURATION
UNSPECIFIED DIM REFER TO SHEET 1



FOR PART 2-6450840-1 ONLY

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
CHK
APPD

14DEC2007
ALEX SHOAL
Sunny Zhao
Sunny Zhao
Z0DEC2007

DIMENSIONS:
INCHES

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC
ANGLES
FINISH

±
±.01
±.005
±.0050
±2°
-

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

108-2292
APPLICATION SPEC
114-13251

MATERIAL

-

Customer Drawing

NAME

RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE

A1

CAGE CODE

100779

DRAWING NO

6450840

RESTRICTED TO

-

SCALE

1:1

SHEET

3

OF


16

REV


H4



PART NUMBER	ROWS		POWER												SIGNAL												POWER								
			P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	1	2	3	4	5	6	7	8	9	10	11	12	LP1	LP2	LP3	LP4	LP5	LP6	LP7	LP8	
6450840-3	D		TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	LT	LT	LT	LT	LT	LT	LT	LT		
	Y5													Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5										
	R5													R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5										
	O5													O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5										
12P + 48S + 8LP																																			



PART NUMBER	ROWS		POWER				SIGNAL												POWER																
			P1	P2	P3	P4	I	2	3	4	5	6	7	8	9	10	11	12	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16					
6450840-4	D		TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT					
	Y5						Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5															Y5	Y5		
	R5						R5	R5	R5	R5	R5	R5	R5	R5	R5	R5	R5															R5	R5		
	O5	O5					O5	O5	O5	O5	O5	O5	O5	O5	O5	O5	O5															O5			
A	HD																														HD				
4ACP + 48S + 12HDP																																			



HOLD DOWN	HD
.120 SIGNAL PRESS FIT CON, ROW A,MLBF	O1
.120 SIGNAL PRESS FIT CON, ROW B,MLBF	R1
.120 SIGNAL PRESS FIT CON, ROW C,MLBF	Y1
.120 SIGNAL PRESS FIT CON, ROW D,MLBF	Z1
.120 SIGNAL PRESS FIT CON, ROW A,STD	O5
.120 SIGNAL PRESS FIT CON, ROW B,STD	R5
.120 SIGNAL PRESS FIT CON, ROW C,STD	Y5
.120 SIGNAL PRESS FIT CON, ROW D,STD	Z5
.120 PRESS FIT LOWER POWER CON	LT
.120 PRESS FIT POWER CON	TT
DESCRIPTION	IDENTIFIER



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 14DEC2007 ALEX SHOAL CHK 20DEC2007 Sunny Zhao APPR 20DEC2007 Sunny Zhao		 TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 1 PLC ±. 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0020 ANGLES ±°		NAME RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE	
		PRODUCT SPEC 108-2292 APPLICATION SPEC 114-13251		SIZE CAGE CODE DRAWING NO A100779C6450840	
MATERIAL -		WEIGHT -		RESTRICTED TO -	
FINISH -		Customer Drawing		SCALE 1:1 SHEET 4 OF 16 REV H	


LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-


PART NUMBER	ROWS		POWER					SIGNAL						POWER					
			P1	P2	P3	P4	P5	1	2	3	4	5	6	P6	P7	P8	P9	P10	
6450840-5	D		TT	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	TT	TT	
	Y5							Y5	Y5	Y5	Y5	Y5							
	R5							R5	R5	R5	R5	R5							
	O5							O5	O5	O5	O5	O5							
5P + 24S + 5P																			

PART NUMBER	ROWS		POWER					SIGNAL								POWER		
			P1	P2	P3	P4	P5	1	2	3	4	5	6	7	8	LP1	LP2	
6450840-6	D		TT	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z1	LT		
	C							Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5			
	B							R5	R5	R5	R5	R5	R5	R5	R5			
	A							O5	O5	O5	O5	O5	O5	O5	O5			
5P + 32S + 2LP																		

NO CONTACT LOADED




PART NUMBER	ROWS		POWER				SIGNAL		POWER																																																																																																							
			P1	P2	P3	P4	I	Z	P5	P6	P7	P8																																																																																																				
I-6450840-0	D						T5	T5																																																																																																								

4805 (3/11)



LOC		DIST		REVISONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
-	-	SEE SHEET 1		-	-	-	

PART NUMBER	ROWS		POWER				SIGNAL					POWER				
			P1	P2	P3	P4	1	2	3	4	5	P5	P6	P7	P8	
1-6450840-1	D	HD	TT	TT	TT	TT	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	TT	HD
	C						Y5	Y5	Y5	Y5	Y5					
	B						R5	R5	R5	R5	R5					
4HDP + 20S + 4HDP	A						O5	O5	O5	O5	O5					



FOR PART NUMBER 6450840-2
UNSPECIFIED DIM REFER TO SHEET 1

PART NUMBER	ROWS		POWER				SIGNAL						POWER			
			P1	P2	P3	LP1	1	2	3	4	5	6	P4	P5	P6	
6450840-2	D	HD	TT	TT	TT	LT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	HD
	C						Y5	Y5	Y5	Y5	Y5	Y5				
	B						R5	R5	R5	R5	R5	R5				
3P + 1LP + 24S + 3HDP	A						O5	O5	O5	O5	O5	O5				



THIS DRAWING IS A CONTROLLED DOCUMENT.

OWN: ALEX SHOAL
CHK: Sunny Zhao
APVD: Sunny Zhao

DATE: 14DEC2007
REV: 20DEC2007

DIMENSIONS:
INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±.01
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.005
ANGLES ±.005
FINISH #2

PRODUCT SPEC
108-2292

APPLICATION SPEC
114-13251

WEIGHT
-

Customer Drawing

NAME
RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

SIZE
A1

CAGE CODE
100779

DRAWING NO
C=6450840

RESTRICTED TO
-

SCALE
1:1

SHEET
8

OF
16



REV
H4

TE Connectivity

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
ES	00	-	-	SEE SHEET 1	-	-


PART NUMBER	ROWS		POWER						SIGNAL						POWER						
			P1	P2	P3	P4	P5	P6	1	2	3	4	5	6	P7	P8	P9	P10	P11	P12	
1-6450840-2	D C B A	HD						Z5	Z5	Z5	Z5	Z5	Z5							HD	
								Y5	Y5	Y5	Y5	Y5	Y5								
								R5	R5	R5	R5	R5	R5								
								O5	O5	O5	O5	O5	O5								
6HDP + 24S + 6HDP																					

PART NUMBER	ROWS		LOW POWER																		SIGNAL						POWER		
			LP1	LP2	LP3	LP4	LP5	LP6	LP7	LP8	LP9	LP10	LP11	LP12	LP13	LP14	LP15	LP16	LP17	LP18	1	2	3	4	5	6	P1	P2	
2-6450840-0	D		LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	LT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT		
	C																			Y5	Y5	Y5	Y5	Y5	Y5				
	B																			R5	R5	R5	R5	R5	R5				R5
	A																			O5	O5	O5	O5	O5	O5				O5
18LP + 24S + 2P																													



LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-


PART NUMBER	ROWS		POWER								SIGNAL		POWER								
			P1	P2	P3	P4	P5	P6	P7	P8	1	2	P9	P10	P11	P12	P13	P14	P15	P16	
1-6450840-6	D C B A										Z5	Z5									
											Y5	Y5									
											R5	R5									
											O5	O5									
8P + 8S + 8P																					



THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN ALEX SHOAL	14DEC2007	 TE Connectivity		
			CHK Sunny Zhao	20DEC2007			
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Sunny Zhao	20DEC2007	NAME RIGHT ANGLE HEADER W/ LP CONTACT AND SHORT END MODULES MULTI-BEAM XLE	
		0 PLC ±.01		PRODUCT SPEC			
		1 PLC ±.01		108-2292			
		2 PLC ±.005		APPLICATION SPEC			
		4 PLC ±.0050		114-13251			
		ANGLES ±2°		WEIGHT -			
MATERIAL -		FINISH -		Customer Drawing			
			A100779C=6450840				
			SCALE 1:1 SHEET 10 OF 16 REV H4				

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER		SIGNAL								LOW POWER				POWER																				
			P1	P2	I	2	3	4	5	6	7	8	LP1	LP2	LP3	LP4	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16							
2-6450840-1	D		TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	Z5	Z5	LT	LT	LT	LT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT	TT		
	C				Y5	Y5	Y5	Y5	Y5	Y5	Y5	Y5																									Y5
	B				R5	R5	R5	R5	R5	R5	R5	R5																									R5
	A	HD			O5	O5	O5	O5	O5	O5	O5	O5																									O5
2P + 32S + 4LP + 14P																																					



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
CHK
APVD

ALEX SHOAL
Sunny Zhao
Sunny Zhao

14DEC2007
20DEC2007
20DEC2007

DIMENSIONS:
INCHES

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC
ANGLES
FINISH

±"
±.01
±.005
±.0050
#2°
-

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

PRODUCT SPEC
APPLICATION SPEC
DRAWING NO
WEIGHT

108-2292
114-13251
-

NAME
RESTRICTED TO

RIGHT ANGLE HEADER
W/ LP CONTACT AND SHORT END MODULES
MULTI-BEAM XLE

A100779C=6450840
-

Customer Drawing

SCALE
SHEET
OF
REV

1:1
11
16
H4



TE Connectivity

TE

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER				SIGNAL			POWER				
			P1	P2	P3	P4	1	2	3	P5	P6	P7	P8	
2-6450840-2	D		TT	TT	TT	TT	Z5	Z5	Z5	TT	TT	TT	TT	
	C						Y5	Y5	Y5					
	B						R5	R5	R5					
	A						HD							
4P + 12S + 4P														

PART NUMBER	ROWS		POWER		SIGNAL				POWER		
			P1	P2	1	2	3	4	P3	P4	
2-6450840-5	D		TT	TT	Z5	Z5	Z5		TT	TT	
	C				Y5	Y5	Y5				
	B				R5	R5	R5				
	A				O5	O5	O5				
		HD								HD	
2P + 16S + 2P											



G 8


4805 (3/11)

G7

4805 (3/11)


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
ES	00	-		SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER			SIGNAL						POWER			
			P1	P2	P3	1	2	3	4	5	6	P4	P5	P6	
2-6450840-9	D		TT	TT	TT	Z5	Z5	Z5	Z5	Z5	Z5	TT	TT	TT	
	Y5					Y5	Y5	Y5	Y5	Y5					
	R5					R5	R5	R5	R5	R5					
	01					05	05	05	05	05					
3P + 24S + 3P															



H2

PART NUMBER	ROWS		LOW POWER		SIGNAL				LOW POWER		
			LP1	LP2	1	2	3	4	LP3	LP4	
3-6450840-1	D		LT	LT	Z1	Z5	Z5	Z5	LT	LT	
	C				Y5	Y5	Y5	Y5			
	B				R5	R5	R5	R5			
	A				05	05	05	05			
2LP + 16S + 2LP											



C