






1	2	3	4	5	6	7	8
REV.	ECN NO.	DATE	SIGN	DESCRIPTION			



Pin Assignments
Front View 前視圖

Note:

- * Seals B1 for Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$
(防水墊圈B1線徑: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$)
- * Seals B2 for Cable OD: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$
(防水墊圈B2線徑: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$)
- * One Set Unassembled in One PE Bag
(每一組未組裝, 放置於一個PE袋, 並封口)
- * Important Dimension.
- * Waterproof Rate : IP66
- * Ring: Black, EPDM
- * Housing: Black, Nylon+GF
- * Pin: Copper Alloy, Gold Plated
- * Lock Nut: Black, Nylon+GF
- * Seals: Black, EPDM
- * Clamping Ring: Black, Nylon
- * Sealing Nut: Black, Nylon
- * PE Bag: 90mm*85mm
- * Liquid Glue: Clear

UNIT: mm		TOLERANCE		TITLE		ITEM NO.	DRAWN BY	DATE
.X ±0.25		.XX ±0.1		Standard, Assy Lock 2Pin F Conn M Pin		BB-02BFMA-LL6001	SamChang	2012-03-14
.XXX ±0.05		ANGLES ±1°		SCALE	SIZE	DWG NO.	CHECKED BY	DATE
1:1		A4		REV.	WC-REV.	BB-02BFMA-LL6001	Jeffrey	2012-03-20
A		A.4		SHEET 1 OF 1		CUSTOMER	APPROVED BY	DATE
QC: Inspection item		ALTW		Kevin		2012-03-20		8

Amphenol LTW
安費諾亮泰企業股份有限公司