




## HEYClip™ Nylon Push-In and Thick Panel Push-In Fasteners

ALL NEW PRODUCTS!

### Assembled Panel Thickness Sequence

- **Slotted leg design** allows for both compression through the mounting hole and then expansion back to original shape—to lock assembled components securely.
- May be disassembled and reused.
- Offer a low cost way to assemble metal, plastic, composite, wood, and other thin gauge materials.
- Snap into mounting holes with fingertip pressure—no tools required.
- Vibration, abrasion, and corrosion resistant.



| ASSEMBLED<br>PANEL<br>THICKNESS                            |     | MOUNTING<br>HOLE DIA. |     | PART NO. |                                                                                         | DESCRIPTION | PART DIMENSIONS |      |                |     |                |      |                  |     |
|------------------------------------------------------------|-----|-----------------------|-----|----------|-----------------------------------------------------------------------------------------|-------------|-----------------|------|----------------|-----|----------------|------|------------------|-----|
|                                                            |     |                       |     | Natural  |  Black |             | A<br>Length     |      | B<br>Clip Dia. |     | C<br>Head Dia. |      | D<br>Head Height |     |
| in.   mm.                                                  |     | in.   mm.             |     |          |                                                                                         |             | in.   mm.       |      | in.   mm.      |     | in.   mm.      |      | in.   mm.        |     |
| PF Series    For combined Panel Thickness ≤ .250" (6,4 mm) |     |                       |     |          |                                                                                         |             |                 |      |                |     |                |      |                  |     |
| .07                                                        | 1,7 | .165                  | 4,2 | 0351     | 0351B                                                                                   | PF 065-165  | .20             | 5,1  | .20            | 5,1 | .34            | 8,7  | .12              | 3,1 |
| .09                                                        | 2,4 | .093                  | 2,4 | 0340     | 0340B                                                                                   | PF 093-093* | .17             | 4,3  | .11            | 2,7 | .28            | 7,1  | .03              | 0,7 |
| .10                                                        | 2,5 | .245                  | 6,2 | 0384     | 0384B                                                                                   | PF 098-245  | .27             | 6,8  | .28            | 7,1 | .50            | 12,7 | .06              | 1,4 |
| .12                                                        | 2,9 | .125                  | 3,2 | 0339     | 0339B                                                                                   | PF 115-125  | .20             | 5,1  | .15            | 3,7 | .25            | 6,4  | .04              | 1,0 |
| .12                                                        | 3,1 | .089                  | 2,3 | 0341     | 0341B                                                                                   | PF 121-089* | .21             | 5,3  | .15            | 3,7 | .31            | 7,9  | .04              | 1,0 |
|                                                            |     | .115                  | 2,9 | 0347     | 0347B                                                                                   | PF 121-115  | .25             | 6,2  | .14            | 3,6 | .20            | 5,2  |                  |     |
|                                                            |     | .200                  | 5,1 | 0358     | 0358B                                                                                   | PF 121-200  | .27             | 6,9  | .24            | 6,1 | .47            | 11,9 |                  |     |
| .13                                                        | 3,4 | .175                  | 4,4 | 0350     | 0350B                                                                                   | PF 133-175  | .27             | 6,9  | .20            | 5,1 | .34            | 8,7  | .04              | 1,0 |
| .16                                                        | 4,0 | .115                  | 2,9 | 0343     | 0343B                                                                                   | PF 156-115  | .29             | 7,4  | .14            | 3,6 | .20            | 5,2  | .04              | 1,0 |
|                                                            |     | .210                  | 5,3 | 0360     | 0360B                                                                                   | PF 156-210  | .31             | 7,8  | .23            | 5,8 | .47            | 11,9 | .05              | 1,3 |
| .17                                                        | 4,3 | .260                  | 6,6 | 0370     | 0370B                                                                                   | PF 171-260  | .36             | 9,1  | .30            | 7,5 | .59            | 15,1 | .06              | 1,5 |
| .19                                                        | 4,8 | .155                  | 3,9 | 0342     | 0342B                                                                                   | PF 190-155  | .28             | 7,1  | .18            | 4,6 | .20            | 5,2  | .04              | 1,0 |
| .24                                                        | 6,0 | .200                  | 5,1 | 0352     | 0352B                                                                                   | PF 237-200  | .39             | 9,8  | .24            | 6,0 | .47            | 11,9 | .05              | 1,3 |
| .25                                                        | 6,4 | .200                  | 5,1 | 0353     | 0353B                                                                                   | PF 250-200  | .42             | 10,8 | .22            | 5,7 | .34            | 8,7  | .06              | 1,5 |
|                                                            |     | .218                  | 5,5 | 0362     | 0362B                                                                                   | PF 250-218  | .36             | 9,1  | .28            | 7,2 | .41            | 10,3 | .05              | 1,1 |
|                                                            |     | .240                  | 6,1 | 0371     | 0371B                                                                                   | PF 250-240  | .43             | 10,9 | .30            | 7,5 | .59            | 15,1 | .06              | 1,5 |

### PFT Series For combined Panel Thickness > .250" (6,4 mm)

|      |      |      |     |             |   |            |      |      |     |      |     |      |     |     |
|------|------|------|-----|-------------|---|------------|------|------|-----|------|-----|------|-----|-----|
| .27  | 6,9  | .155 | 4,0 | <b>0303</b> | - | PFT 27-16  | .40  | 10,0 | .21 | 5,3  | .38 | 9,5  | .07 | 1,7 |
| .27  | 6,9  | .240 | 6,1 | <b>0308</b> | - | PFT 27-24  | .46  | 11,7 | .30 | 7,6  | .45 | 11,4 | .06 | 1,5 |
| .28  | 7,0  | .240 | 6,1 | <b>0310</b> | - | PFT 28-24  | .46  | 11,7 | .30 | 7,6  | .45 | 11,4 | .04 | 1,0 |
| .32  | 8,1  | .157 | 4,0 | <b>0312</b> | - | PFT 32-16  | .43  | 10,9 | .21 | 5,3  | .39 | 9,9  | .05 | 1,3 |
| .32  | 8,1  | .118 | 3,0 | <b>0319</b> | - | PFT 32-12  | .40  | 10,2 | .15 | 3,7  | .23 | 5,9  | .03 | 0,8 |
| .34  | 8,6  | .174 | 4,4 | <b>0322</b> | - | PFT 34-17  | .51  | 13,0 | .25 | 6,4  | .33 | 8,4  | .07 | 1,8 |
| .37  | 9,4  | .245 | 6,2 | <b>0323</b> | - | PFT 37-25  | .55  | 14,0 | .30 | 7,6  | .59 | 15,0 | .13 | 3,3 |
| .38  | 9,7  | .200 | 5,1 | <b>0361</b> | - | PFT 38-20  | .51  | 13,0 | .24 | 6,0  | .34 | 8,7  | .04 | 1,0 |
|      |      | .240 | 6,1 | <b>0327</b> | - | PFT 38-24  | .56  | 14,2 | .30 | 7,6  | .59 | 15,0 | .06 | 1,5 |
| .40  | 10,2 | .135 | 3,4 | <b>0329</b> | - | PFT 40-14  | .54  | 13,7 | .16 | 4,1  | .28 | 7,1  | .08 | 2,0 |
| .41  | 10,3 | .275 | 7,0 | <b>0330</b> | - | PFT 41-28  | .57  | 14,5 | .32 | 8,1  | .59 | 15,0 | .06 | 1,5 |
| .43  | 10,8 | .135 | 3,4 | <b>0331</b> | - | PFT 43-14  | .64  | 16,3 | .16 | 4,1  | .42 | 10,7 | .09 | 2,3 |
| .48  | 12,2 | .240 | 6,1 | <b>0332</b> | - | PFT 48-24  | .67  | 17,0 | .30 | 7,6  | .59 | 15,0 | .06 | 1,5 |
| .55  | 14,0 | .180 | 4,6 | <b>0333</b> | - | PFT 55-18  | .71  | 18,0 | .23 | 5,8  | .35 | 8,9  | .07 | 1,8 |
| .70  | 17,8 | .245 | 6,2 | <b>0334</b> | - | PFT 70-25  | .90  | 22,9 | .34 | 8,6  | .50 | 12,7 | .08 | 2,0 |
| .88  | 22,4 | .246 | 6,3 | <b>0335</b> | - | PFT 88-24  | 1.12 | 28,5 | .28 | 7,1  | .38 | 9,7  | .06 | 1,5 |
|      |      | .250 | 6,4 | <b>0336</b> | - | PFT 88-25  | 1.13 | 28,7 | .31 | 7,9  |     |      |     |     |
| .89  | 22,6 | .260 | 6,6 | <b>0337</b> | - | PFT 89-26  | .95  | 24,1 | .34 | 8,6  | .41 | 10,4 | .07 | 1,8 |
| 1.00 | 25,4 | .345 | 8,9 | <b>0338</b> | - | PFT 100-35 | 1.38 | 35,1 | .45 | 11,4 | .50 | 12,7 | .07 | 1,8 |
| 1.02 | 25,9 | .350 | 8,9 | <b>0344</b> | - | PFT 102-35 | 1.40 | 35,6 | .48 | 12,2 | .50 | 12,7 | .06 | 1,5 |

Standard color natural. Consult Heyco for black and other colors.

\*No slot.

Quick  
Specs

|                     |                            |
|---------------------|----------------------------|
| Material            | Nylon 6/6                  |
| Flammability Rating | 94V-2                      |
| Temperature Range   | 32°F (0°C) to 185°F (85°C) |