HEYClip™ Nylon Arrow Clips

Maximum Assembled Panel Sequence

- **Hollow body design** allows the clip to compress through the mounting hole, then expand back to original shape to lock assembled components securely (PN 0306 does not have a hollow body).
- May be disassembled and reused.
- Offer a low cost way to assemble metal, plastic, composite, wood, and other thin gauge materials.
- Snap into mounting holes with fingertip pressure–no tools required.
- Vibration, abrasion, and corrosion resistant.



AC/ACT Series

Assembled Panel Thickness Range Maximum in.	Maximum mm.	Minimum in.	Minimum mm.	Mounting Hole Diameter Range Maximum in.	Maximum mm.	Minimum in.	Minimum mm.	Part No. Natural	Part No. Black	Description	Part Dimensions A Length in.	A Length mm.	B Clip Dia. in.	B Clip Dia. mm.	C Head Dia. in.	C Head Dia. mm.	D Head Height in.	D Head Height mm.
AC Series For combined Panel Thickness ≤ .250" (6,4 mm)																		
.10	2,5	.04	1,0	.190	4,8	.180	4,6	**0325**	**0325B**	AC 1996	.45	11,4	.22	5,5	.36	9,1	.06	1,5
.13	3,2	.06	1,6	.122	3,1	.118	3,0	**0315**	**0315B**	AC 15	.39	9,9	.15	3,8	.28	7,1		
				.135	3,4	.130	3,3	**0302**	**0302B**	AC 2	.38	9,7	.16	4,1				
				.165	4,2	.160	4,1	**0318**	**0318B**	AC 18 *	.40	10,2	.19	4,7	.28	7,1	.08	2,0
				.192	4,9	.182	4,6	**0301**	**0301B**	AC 1	.42	10,5	.23	5,7	.36	9,1	.06	1,5
				.212	5,4	.192	4,9	**0328**	**0328B**	AC 28	.45	11,4	.24	6,0	.38	9,5		
				.223	5,7	.213	5,4	**0307**	**0307B**	AC 7	.45	11,4	.22	5,6	.37	9,4		
.14	3,6	.13	3,2	.132	3,4	.130	3,3	**0313**	**0313B**	AC 13	.32	8,1	.16	4,1	.28	7,1		
.15	3,7	.06	1,6	.161	4,1	.151	3,8	**0304**	**0304B**	AC 4	.40	10,2	.18	4,6				
.16	4,1	.06	1,6	.223	5,7	.213	5,4	**0305**	**0305B**	AC 5	.52	13,2	.25	6,3	.37	9,4		
.19	4,7	.17	4,2	.192	4,9	.182	4,6	**0311**	**0311B**	AC 11	.52	13,2	.21	5,2				
		.06	1,6	.223	5,7	.213	5,4	**0326**	**0326B**	AC 1668	.49	12,5	.25	6,3	.63	15,9	.10	2,5
		.13	3,2	.260	6,6	.250	6,4	**0309**	**0309B**	AC 9	.58	14,6	.29	7,4	.48	12,3	.07	1,8
.25	6,4	.13	3,2	.260	6,6	.250	6,4	**0321**	**0321B**	AC 21**	.63	16,0	.28	7,1	.50	12,7	.09	2,2
ACT Series For combined Panel Thickness > .250" (6,4 mm)																		
.30	7,6	.29	7,4	.150	3,8	.145	3,7	**0314**	**0314B**	ACT 14	.53	13,5	.20	5,0	.27	6,9	.07	1,7
.33	8,4	.31	7,9	.192	4,9	.182	4,6	**0306**	**0306B**	ACT 6 **	.55	14,0	.23	5,7	.38	9,7	.06	1,5
.34	8,6	.06	1,6	.335	8,5	.320	8,1	**0317**	**0317B**	ACT 17	.90	22,9	.38	9,5	.68	17,3	.07	1,7
.38	9,7	.36	9,1	.260	6,6	.250	6,4	**0316**	**0316B**	ACT 16	.81	20,6	.28	7,0	.61	15,5		
.75	19,1	.50	12,7	.260	6,6	.250	6,4	**0324**	**0324B**	ACT 24**	1.14	28,8	.29	7,3				

Standard color natural. Consult Heyco for black and other colors.
*AC 18 minimum panel thickness is .03˝ (0,8 mm), head height is .08˝ (2,0 mm)
**Webbed, not hollow body.



HMB Series

HEYClip™ Shorty Mounting Buttons

ALL NEW PRODUCTS!

Assembled Panel Thickness Range Maximum in.	Maximum mm.	Minimum in.	Minimum mm.	Mounting Hole Diameter Range Maximum in.	Maximum mm.	Minimum in.	Minimum mm.	Part No. Natural	Part No. Black	Description	Part Dimensions A Length in.	A Length mm.	B Clip Dia. in.	B Clip Dia. mm.	C Head Dia. in.	C Head Dia. mm.	D Head Height in.	D Head Height mm.
HMB Series																		
.10	2,5	.08	2,0	.127	3,2	.122	3,1	**4199**	**4199B**	HMB 125-06	.33	8,4	.09	2,2	.28	7,1	.05	1,2
.16	4,0	.11	2,9	.141	3,6	.131	3,3	**4200**	**4200B**	HMB 136-06	.44	11,1	.13	3,2	.41	10,3	.07	1,7
.16	4,0	.10	2,5	.192	4,9	.181	4,6	**4201**	**4201B**	HMB 187-06	.43	10,9	.16	4,0	.50	12,7	.09	2,2

Standard color natural and black.

Quick Specs

Material	Nylon 6/6
Flammability Rating	94V-2
Temperature Range	32°F (0°C) to 185°F (85°C)