

## Coaxial Cable Connector 11\_MCX-50-1-14/111\_N

### Description

Straight cable plug

Interface standards

IEC 60169-36\_CECC 22220



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0006 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

### Related Documents

Outline drawing	DOU-00005761
Catalogue drawing	DOU-00005763
Assembly instruction	DOC-0000178634

### Ordering Information

Single package	11_MCX-50-1-14/111_NE
Bulk 100 pcs package	11_MCX-50-1-14/111_NH

### Additional Information

Suitable cables	EZ_47_TP_M17, SUCOFORM_47 CU
-----------------	------------------------------

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[11\\_MCX-50-1-14/111\\_NH](#)