



VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

NOTES:

- 1) CORDAGE: 18/2 SPT-1, 105°C, BLACK
- 2) APPROVALS: UL/CSA WIRING HARNESS.
- 3) RATING: 1 AMP/250 VOLTS
- 4) FLAME RATING : VW1
- 5) CORDAGE DIMENSIONS: .110" X .220" REF.
- 6) CORD IS NOT POLARIZED. RIBBED LEAD WILL NOT ALWAYS BE IN SAME POSITION WITH REFERENCE TO THE CONNECTOR.
- 7) PACKAGING: 100 PIECES PER CARTON.
- 8) ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.

CONNECTOR: PHX707 A
 COLOR: BLACK

CUD

FORM IN71-07 REV.A

Indianapolis, IN
 Conover, N.C.
 Freemont, CA
 Aguascalientes, MX
 Tijuana, Mexico
 Hermosillo, MX
 Clinton, AR
 Kanata, Canada

Proprietary Notice:

This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.

MATERIAL:
 PLUG: PVC, BLACK
 JACKET: PVC, BLACK

FINISH:

REV	DESCRIPTION	DATE
1	C.U.D - NEW RELEASE	9/25/07

SCALE:	EQUI:	ITEM DESCRIPTION	APPROVED	DRAWN BY	DATE:
NDT TO SCALE	N/A	APPLANCE CORD FOR COOLING FAN	STC	STC	9/25/07
TOLERANCE UNLESS OTHERWISE SPECIFIED		PART NO. 17905 10 B1			
.XXX ± .005					
.XX ± .02					
.X ± .03					
FRACT. ± 1/32					
ANGULAR ± 1/2°					