

## Cable marker - UCT-WMTBA (40X17) - 1014086

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable marker, Sheet, white, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Assembly with cable binders, Cable diameter: >6 mm, Lettering field: 40 x 17 mm

### Why buy this product

- The UCT-WMTBA ... UniCard labeling range includes markers that can be secured using standard cable binders
- Thanks to their angular shape the markers fit perfectly onto cables
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements
- The format automatically ensures printing with a high degree of positioning accuracy

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 STK                                                                                                  |
| GTIN                                 | <br>4 046356 781381 |
| Weight per Piece (excluding packing) | 9.62 g                                                                                                  |
| Weight per piece (including packing) | 9.62 g                                                                                                  |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 40 mm |
| Width (a)  | 17 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
|---------------------------------|-------------------|

#### General

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Color                                  | white                                    |
| Components                             | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94 | V0                                       |
| Material                               | PC                                       |
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1)              |
| Number of individual labels            | 3                                        |
| Number of individual labels per row    | 1                                        |
| Marking mounting type                  | Assembly with cable binders              |

## Cable marker - UCT-WMTBA (40X17) - 1014086

### Technical data

#### Standards and Regulations

|                                        |                             |
|----------------------------------------|-----------------------------|
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0                          |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190218 |
| eCl@ss 4.1 | 24190218 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 8.0 | 27149129 |
| eCl@ss 9.0 | 27400629 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC001530 |
| ETIM 5.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>